



Electric pedestrian stacker with support arm lift

ERD 220i

Lift height: 1660-3760 mm / Load capacity: 2000 kg

ERD 220i



ERD 220i

VDI table

Stand-on: 07/2024

Characteristic	1.1	Manufacturer (abbreviated description)		Jungheinrich
	1.2	Manufacturer's type designation		ERD 220i
	1.3	Drive		Electric
	1.4	Operation		Tiller
	1.5	Load capacity/load	Q kg	2000
	1.5.1	Rated capacity/load with mast lift	Q kg	1000
	1.5.2	Rated capacity/load with support arm lift	Q kg	2000
	1.6	Load centre distance	c mm	600
	1.8	Load distance, centre of drive axle to fork	x mm	959
	1.9	Wheelbase	y mm	1495
Weights	2.1.1	Service weight (incl. battery)	kg	1055
	2.2	Axle load laden front/rear	kg	1810 / 1245
	2.3	Axle load unladen front/rear	kg	220 / 835
Wheels/suspension system	3.1	Tyres		Polyurethane (PU)
	3.2	Tyre size, front		ø 230x77
	3.3	Tyre size, rear		ø 85x95
	3.4	Additional wheels		ø 140x57
	3.5	Wheels, number front/back (x=driven)		1x +2
	3.6	Tread width, front	b10 mm	512
	3.7	Tread width, rear	b11 mm	385
Basic dimensions	4.2	Retracted mast height (h1)	h1 mm	1505
	4.3	Free lift (h2)	h2 mm	100
	4.4	Lift (h3)	h3 mm	2010
	4.5	Extended mast height (h4)	h4 mm	2475
	4.6	Initial lift	h5 mm	120
	4.9	Height of tiller handle in drive position min./max.	h14 mm	1215 / 1275
	4.15	Height, lowered	h13 mm	94
	4.19	total length	l1 mm	2358
	4.20	Length including fork shank	l2 mm	1168
	4.21.1	total width	b1 mm	770
	4.22	Fork dimensions	s/e/l mm	56 x 185 x 1190
	4.25	Width across forks	b5 mm	570
	4.32	Ground clearance centre of wheelbase	m2 mm	18
	4.34.1	Aisle width (pallet 1000x1200 sideways)	Ast mm	2564
	4.34.2	Aisle width (pallet 800x1200 length)	Ast mm	2574
4.35	Turning radius	Wa mm	2133	
Performance data	5.1	Travel speed laden/unladen (Efficiency drivePLUS)	km/h	9 / 12.5 9 / 14
	5.2	Lift speed laden/unladen	m/s	0.21 / 0.37
	5.3	Lowering speed laden/unladen	m/s	0.49 / 0.44
	5.7	Gradeability laden/unladen	%	8 / 16
	5.8	Max. gradeability laden/unladen	%	8 / 16
	5.10	Service brake		generative
E-motor/ Electronics	6.1	Drive motor, performance S2 60 min (Efficiency drivePLUS)	kW	2.8 3.2
	6.2	Lift motor, performance with S3	kW	2.2
	6.3	Battery according to DIN 43531/35/36		Jungheinrich Li-ion
	6.4	Battery voltage/nominal capacity	V / Ah	24 / 260
	6.5	Battery weight	kg	100

	6.6.1	Energy consumption according to EN cycle (Efficiency PLUS)	kWh/h	0.6 0.65
	6.6.2	CO2 equivalent as per EN 16796 (Efficiency PLUS)	kg/h	0.3 0.4
	6.7	Throughput (Efficiency PLUS)	t/h	100 106
	6.8	Turnover efficiency according to VDI 2198 (Efficiency PLUS)	t/kWh	106 105
	6.8.1	Energy consumption with max. throughput (Efficiency PLUS)	kWh/h	0.94 1.01
Other	10.7	Sound level as per EN12053, operator's ear	dB (A)	67.1
<p>- This data sheet according to VDI guideline 2198 only states the technical values of the standard truck. Different tyres, other masts, additional equipment etc. may result in different values.</p>				

The values in the table apply for the fixed stand-on platform, integrated M battery compartment, ZT2010 mast without overhead guard, raised support arm lift.

Entry height for stand-on platform: 202 / 214 mm (stand-on platform standard / stand-on platform suspension adjustable).

Ground clearance at end of stand-on platform: 117 / 98 mm (stand-on platform standard / stand-on platform compact).

An overhead guard is optionally available and compulsory for masts with $h_3 > 2,300$ mm. (VDI no. 4.7 height of overhead guard: $h_6 = 2,300$ mm; VDI no. 4.8 stand height with unladen stand-on platform: $h_7 = 2,037 / 2,025$ mm (stand-on platform standard / stand-on platform suspension adjustable)).

- VDI no. 1.5: in double-decker mode: mast lift max. 1 t / overall load max. 2 t.
- VDI no. 1.8: lowered support arm lift: $x + 46$ mm. With fork length 1,150 mm: $x - 40$ mm. With DZ mast: $x - 18$ mm.
- VDI no. 1.9: lowered support arm lift: $y + 46$ mm. With fork length 1,150 mm: $y - 40$ mm.
- VDI no. 4.19: with fork length 1,150 mm: $l_1 - 40$ mm. with compact stand-on platform: $l_1 - 103$ mm. With DZ mast: $l_1 + 18$ mm.
- VDI no. 4.20: with compact stand-on platform: $l_2 - 103$ mm. With DZ mast: $l_2 + 18$ mm.
- VDI no. 4.34.1: with fork length 1,150 mm: aisle width - 40 mm. With compact stand-on platform: aisle width - 103 mm. With DZ mast: aisle width + 18 mm.
- VDI no. 4.34.2: with fork length 1,150 mm: aisle width - 40 mm. With compact stand-on platform: aisle width - 103 mm. With DZ mast: aisle width + 10 mm.
- VDI no. 4.35: lowered support arm lift: $W_a + 46$ mm. with fork length 1,150 mm: $W_a - 40$ mm. With compact stand-on platform: $W_a - 103$ mm.

The German production facilities in
Norderstedt, Moosburg and Landsberg
are certified as well as our Genuine Parts
Center in Kaltenkirchen. ISO 9001
ISO 14001

Jungheinrich fork lift trucks meet
European safety requirements. 

 **JUNGHEINRICH**