



## Medium/high level order picker **EKS 210**

Lift height: 2800-4750 mm / Load capacity: 1000 kg

**EKS 210**

# VDI table

Stand-on: 07/2024

Characteristic	1.1	Manufacturer (abbreviated description)		Jungheinrich		
	1.2	Manufacturer's type designation		EKS 210 Z	EKS 210 L	EKS 210 O
	1.3	Drive		Electric		
	1.4	Operation		Order pickers		
	1.5	Load capacity/load	Q kg	1000		
	1.6	Load centre distance	c mm	600		
	1.8	Load distance, centre of drive axle to fork	x mm	155		
	1.9	Wheelbase	y mm	1425		
	Weights	2.1.1	Service weight (incl. battery)	kg	2400	
2.2		Axle load laden front/rear	kg	2650 / 750	2680 / 720	2605 / 705
2.3		Axle load unladen front/rear	kg	1150 / 1250	1180 / 1220	1105 / 1245
Wheels/ suspension system	3.1	Tyres		Polyurethane (PU)		
	3.2	Tyre size, front		Ø 150 x 100		
	3.3	Tyre size, rear		Ø 230 x 83		
	3.5	Wheels, number front/back (x=driven)		4 / 1 x		
Basic dimensions	4.2	Retracted mast height (h1)	h1 mm	2325		
	4.4	Lift (h3)	h3 mm	2800		
	4.5	Extended mast height (h4)	h4 mm	5125		
	4.7	Height of overhead guard (cab)	h6 mm	2325		
	4.8.1	Stand height	h7 mm	200		
	4.14	Stand height, elevated	h12 mm	3000		
	4.15	Height, lowered	h13 mm	60		
	4.19	total length	l1 mm	2995	3040	2985
	4.20	Length including fork shank	l2 mm	1795	1785	
	4.21.1	total width	b1 mm	900		
	4.22	Fork dimensions	s/ e/l mm	40 x 100 x 1200	50 x 100 x 1250	50 x 100 x 1200
	4.25	Width across forks	b5 mm	560		
	4.31	Ground clearance laden under mast	m1 mm	50		
4.35	Turning radius	Wa mm	1565			
Performance data	5.1	Travel speed laden/unladen	km/h	10 / 10		
	5.2	Lift speed laden/unladen	m/s	0.25 / 0.3		
	5.3	Lowering speed laden/unladen	m/s	0.3 / 0.25		
	5.10	Service brake		regenerative		
	5.11	Parking brake		Electric sprung-loaded		
E-motor/ Electronics	6.1	Drive motor, performance S2 60 min	kW	3.2		
	6.2	Lift motor, performance with S3	kW	8		
	6.3	Battery according to DIN 43531/35/36		5 PzS 775		
	6.4	Battery voltage/nominal capacity	V / Ah	24 / 775		
	6.5	Battery weight	kg	600		
Other	8.1	Type of drive control		AC drive control system		
	10.5	Steering version		electric		
	10.7	Sound level as per EN12053, operator's ear	dB (A)	60		

- This data sheet according to VDI guideline 2198 only states the technical values of the standard truck. Different tyres, other masts, additional equipment etc. may result in different values.

The German production facilities in  
Norderstedt, Moosburg and Landsberg  
are certified as well as our Genuine Parts  
Center in Kaltenkirchen. ISO 9001  
ISO 14001

Jungheinrich fork lift trucks meet  
European safety requirements. 

**JUNGHEINRICH**