



Electric reach truck

ETV 216i

Lift height: 4550-10700 mm / Load capacity: 1600 kg

ETV 216i



ETV 216i

VDI table

Stand-on: 07/2024

Characteristic	1.1	Manufacturer (abbreviated description)		Jungheinrich
	1.2	Manufacturer's type designation		ETV 216i
	1.3	Drive		Electric
	1.4	Operation		Sideways-seated
	1.5	Load capacity/load	Q kg	1600
	1.6	Load centre distance	c mm	600
	1.8	Load distance, centre of drive axle to fork	x mm	401
	1.8.1	Load distance, centre of drive axle to fork, mast extended	mm	215
	1.9	Wheelbase	y mm	1410
Weights	2.1.1	Service weight (incl. battery)	kg	3438
	2.3	Axle load unladen front/rear	kg	2292 / 1146
	2.4	Axle load fork forward laden front/rear	kg	902 / 4132
	2.5	Axle load fork back laden front/rear	kg	2024 / 3014
Wheels/suspension system	3.1	Tyres		Polyurethane (PU)
	3.2	Tyre size, front		Ø 343 x 114
	3.3	Tyre size, rear		Ø 285 x 100
	3.5	Wheels, number front/back (x=driven)		1x / 2
	3.7	Tread width, rear	b11 mm	1168
Basic dimensions	4.1	Forward/backward tilt of mast	a/β °	1 / 3
	4.2	Retracted mast height (h1)	h1 mm	2300
	4.3	Free lift (h2)	h2 mm	1646
	4.4	Lift (h3)	h3 mm	5300
	4.5	Extended mast height (h4)	h4 mm	5954
	4.7	Height of overhead guard (cab)	h6 mm	2263
	4.8	Seat height/stand height	h7 mm	1079
	4.10	Height of support arms	h8 mm	309
	4.19	total length	l1 mm	2419
	4.20	Length including fork shank	l2 mm	1269
	4.21.1	total width	b1 mm	1282
	4.21.2	total width	b2 mm	1270
	4.22	Fork dimensions	s/e/l mm	40 x 120 x 1150
	4.23	Fork carriage connection class		2B
	4.24	Fork carriage width	b3 mm	830
	4.25	Width across forks	b5 mm	335
	4.25.1	Width across forks (min./max.)	b5 mm	335 / 705
	4.26	Width between support arms/loading areas	b4 mm	940
	4.28	Reach distance	mm	616
	4.32	Ground clearance centre of wheelbase	m2 mm	80
	4.34.1	Aisle width (pallet 1000x1200 sideways)	Ast mm	2713
4.34.2	Aisle width (pallet 800x1200 length)	Ast mm	2759	
4.35	Turning radius	Wa mm	1665	
4.37	Length over the support arms	L7 mm	1837	
Performance data	5.1	Travel speed laden/unladen (Efficiency drivePLUS)	km/h	11 / 11 14 / 14
	5.2	Lift speed laden/unladen (Efficiency liftPLUS)	m/s	0.35 / 0.7 0.59 / 0.81
	5.3	Lowering speed laden/unladen (Efficiency liftPLUS)	m/s	0.56 / 0.56 0.56 / 0.56
	5.4	Reach speed laden/unladen (Efficiency liftPLUS)	m/s	0.18 / 0.18 0.24 / 0.24
	5.7	Gradeability laden/unladen (Efficiency drivePLUS)	%	8 / 12 8 / 12
	5.8	Max. gradeability laden/unladen (Efficiency drivePLUS)	%	10 / 15 10 / 15

	5.9	Acceleration time laden/unladen (Efficiency drivePLUS)	s	5.1 / 4.9 4.7 / 4.3
	5.10	Service brake		electric
E-motor/Electronics	6.1	Drive motor, performance S2 60 min (Efficiency drivePLUS)	kW	6 8.5
	6.2	Lift motor, performance with S3 (Efficiency liftPLUS)	kW	13.3 15.5
	6.4	Battery voltage/nominal capacity	V / Ah	51.2 / 390
	6.6	Energy consumption according to VDI cycle	kWh/h	3.3
	6.6.1	Energy consumption according to EN cycle (Efficiency PLUS)	kWh/h	3.19 3.34
	6.6.2	CO2 equivalent as per EN 16796 (Efficiency PLUS)	kg/h	1.7 1.8
	6.7	Throughput (Efficiency PLUS)	t/h	59.68 71.2
	6.8.1	Energy consumption with max. throughput (Efficiency PLUS)	kWh/h	3.09 4.18
Other	10.1	Operating pressure for attachment	bar	150
	10.2	Oil flow for attachments	l/min	20
	10.7	Sound level as per EN12053, operator's ear	dB (A)	70
- This data sheet according to VDI guideline 2198 only states the technical values of the standard truck. Different tyres, other masts, additional equipment etc. may result in different values.				

- Efficiency: Values of standard package | PLUS: Values of performance package
- VDI no. 1.8: the mast type influences the load distance, centre of drive axle to fork x
 - VDI no. 2.1.1: battery size and mast version affect service weight and axle loads
 - VDI no. 2.3: battery size and mast version affect service weight and axle loads
 - VDI no. 2.4: battery size and mast version affect service weight and axle loads
 - VDI no. 2.5: battery size and mast version affect service weight and axle loads
 - VDI no. 4.1: the mast version determines the tilt values
 - VDI no. 4.19: the mast type and the fork length influence the overall length l1
 - VDI no. 4.20: the mast type influences the length including fork shank l2
 - VDI no. 4.28: the mast type influences the reach distance l4
 - VDI no. 4.34.1: the mast type influences the aisle widths
 - VDI no. 4.34.2: the mast type influences the aisle widths
 - VDI no. 6.6.1: PLUS refers to the drive&liftPLUS performance package
 - VDI no. 6.6.2: PLUS refers to the drive&liftPLUS performance package
 - VDI no. 6.7: PLUS refers to the drive&liftPLUS performance package
 - VDI no. 6.8.1: PLUS refers to the drive&liftPLUS performance package

The German production facilities in
Norderstedt, Moosburg and Landsberg
are certified as well as our Genuine Parts
Center in Kaltenkirchen. ISO 9001
ISO 14001

Jungheinrich fork lift trucks meet
European safety requirements. 

**JUNGHEINRICH**