



Electric tow tractor **EZS 010**

Towing capacity: 1000 kg

EZS 010



EZS 010



EZS 010



VDI table

Stand-on: 11/2024

| | | | | | |
|--------------------------|--------|---|-----|----------------|-----------------|
| Characteristic | 1.1 | Manufacturer (abbreviated description) | | • Jungheinrich | |
| | 1.2 | Manufacturer's type designation | | EZS 010 | |
| | 1.3 | Drive | | Electric | |
| | 1.4 | Operation | | Pedestrian | |
| | 1.5.3 | Towing capacity | Q | kg | 1000 |
| | 1.7 | Rated drawbar pull | | N | 200 |
| | 1.9 | Wheelbase | y | mm | 325 |
| Weights | 2.1 | tare weight | | kg | 67 |
| | 2.3 | Axle load unladen front/rear | | kg | 55 / 19 |
| Wheels/suspension system | 3.2 | Tyre size, front | | | 250x80 |
| | 3.3 | Tyre size, rear | | | 75x32 |
| | 3.5 | Wheels, number front/back (x=driven) | | | 2x+2/- |
| | 3.6 | Tread width, front | b10 | mm | 185 |
| | 3.7 | Tread width, rear | b11 | mm | 385 |
| Basic dimensions | 4.9 | Height of tiller handle in drive position min./max. | h14 | mm | 750 / 1150 |
| | 4.19 | total length | l1 | mm | 915 |
| | 4.21.1 | total width | b1 | mm | 503 |
| | 4.32 | Ground clearance centre of wheelbase | m2 | mm | 35 |
| | 4.35 | Turning radius | Wa | mm | 560 |
| Performance data | 5.1 | Travel speed laden/unladen | | km/h | 4.5 / 4.9 |
| | 5.5 | Drawbar pull laden | | N | 200 |
| | 5.6 | Max. drawbar pull laden/unladen | | N / - | 550 / - |
| | 5.10 | Service brake | | | electromagnetic |
| E-motor/ Electronics | 6.1 | Drive motor, performance S2 60 min | | kW | 0.4 |
| | 6.4 | Battery voltage/nominal capacity | | V / Ah | 24 / 36 |
| | 6.5 | Battery weight | | kg | 7.5 |
| | 6.6.1 | Energy consumption according to EN cycle | | kWh/h | 0.18 |
| | 6.6.2 | CO2 equivalent as per EN 16796 | | kg/h | 0.1 |
| Other | 8.1 | Type of drive control | | | Impulse/DC |
| | 10.7 | Schalldruckpegel nach EN12053 | | dB (A) | 70 |

- This data sheet according to VDI guideline 2198 only states the technical values of the standard truck. Different tyres, other masts, additional equipment etc. may result in different values.

The German production facilities in
Norderstedt, Moosburg and Landsberg
are certified as well as our Genuine Parts
Center in Kaltenkirchen. ISO 9001
ISO 14001

Jungheinrich fork lift trucks meet
European safety requirements. 

 **JUNGHEINRICH**