



Hand pallet truck

AM V05

Lift height: 390 mm / Load capacity: 500 kg

JUNGHEINRICH

The wide tread hand pallet truck for display pallets.

Safe handling of quarter, half and special pallets.

The manoeuvrable and flexible AM V05 are the ideal hand pallet trucks for all situations where quarter, half and special pallets have to be moved. For the transport of display pallets, in retail areas for example, the fork width can be manually adjusted, in the range of 140 to 585 mm, to fit special pallets. For application in retail areas with customer contact the AM V05 run particularly quiet.

The tiller head, which can be used by left- and right-handed operators alike, allows for fatigue-free work shifts, due to its ergonomic design and ensures the manoeuvrability in any situation. With the fast lift and the optimised lowering valve goods can be moved fast, safely and efficiently. By the way, this also counts for standard euro pallets.

As a matter of course you profit with the AM V05 from our high durability with the applied hardened steel, bushed wheels, the welded tiller mounting and the extremely low-maintenance joints.



Proven quality by Jungheinrich

For decades, the Jungheinrich brand has been representing utmost reliability, premium-quality machines and comprehensive service whenever you need it. From hand pallet trucks to fully automated logistics systems – Jungheinrich delivers maximum quality.

All benefits at a glance

- Manually adjustable fork width (140-585 mm)
- Particularly quiet run for usage in retail areas
- Energy and time-saving fast lift for up to 120 kg
- Precise pump hydraulic system and special lowering valve
- Ergonomic tiller for right and left hand use alike

Your Jungheinrich hand pallet truck for maximum customer benefits.



Efficiency

Maximum performance with the most efficient trucks.

Left- and right-handed operators equally benefit from the optimised control element and the decrease of needed pull force due to bushed wheels.

Efficient Handling

- The fast lift (up to 120 kg) ensures that euro pallets can be lifted clear of the ground with just 3 pump strokes.
- The maximum lift height of 390 mm is achieved with only 5 pump strokes.
- Particularly sensitive and controlled lowering of goods with the special lowering valve.
- Optimised hydraulic system for effortless pumping.
- Drawbar pull required is reduced by the bushes on the wheels.
- Smooth controls equally suitable for both left-handed and right-handed operators.



Safety

Best prerequisites for working safely.

Display pallets can be moved safely with this particularly long living hand pallet truck. The abrasion free construction allows for safe operation, every day.

Safe and abrasion free

- Safe transport of display pallets.
- Single entrance rolls out of abrasion free smooth-running nylon.
- Powder coating for corrosion protection of the steel construction.

Maximum stability and durability

- Strong forks and contoured shapes.
- Welded tiller mounting.
- Protected entry rollers.
- Hardened steel.



Individuality

A forklift truck as individual as your business.

This hand pallet truck perfectly adjusts to the pallets you are moving – no matter if it is special pallets or euro pallets.

Quiet and robust

- Robust solid rubber tyres for particularly quiet running.

Wide tread pallet truck

- Individually adjustable forks in the range of 140 to 585 mm for pick up and transport of non-standard carriers.
- Quick loading and unloading of small carriers on a euro pallet are possible.

Overview

The right solution for your applications:

Name	Load capacity/load	Lift height (max.)	Aisle width (pallet 800x1200 length)
AM V05, M V05760x955, C-GN	500 kg	390 mm	2005 mm

The German production facilities in
Norderstedt, Moosburg and Landsberg
are certified as well as our Genuine Parts
Center in Kaltenkirchen.

ISO 9001
ISO 14001

Jungheinrich fork lift trucks meet
European safety requirements.



 **JUNGHEINRICH**

The Jungheinrich logo, featuring a red upward-pointing arrow above the word 'JUNGHEINRICH' in a bold, black, sans-serif font.