



## Hand pallet truck

**AMX I15 / I15 e / I15 p / I15 ep**

Lift height: 710 mm / Load capacity: 1500 kg

**JUNGHEINRICH**

# AMX I15 / I15 e / I15 p / I15 ep



# AMX I15 / I15 e / I15 p / I15 ep



# VDI table

Stand-on: 12/2024

Characteristic	1.1	Manufacturer (abbreviated description)	Jungheinrich									
			AMX I15e	AMX I15ep	AMX I15	AMX I15p						
Characteristic	1.2	Manufacturer's type designation										
	1.3	Drive	Manual									
	1.4	Operation	Manual									
	1.5	Load capacity/load	Q	kg	1500							
	1.6	Load centre distance	c	mm	600							
	1.9	Wheelbase	y	mm	1255							
	Weights	2.1	tare weight	kg	132				125			
2.2		Axle load laden front/rear	kg	753 / 357	753 / 387	720 / 358	750 / 358					
2.3		Axle load unladen front/rear	kg	40 / 100				38 / 70				
Wheels/suspension system	3.1	Tyres	N-BN   V-BV   N-BN   V-BV   N-BN   V-BV   N-BN   V-BV									
	3.2	Tyre size, front	Ø 150x45									
	3.3	Tyre size, rear	Ø 75x68									
	3.5	Wheels, number front/back (x=driven)	2/4									
	3.6	Tread width, front	b10	mm	145							
	3.7	Tread width, rear	b11	mm	440							
	Basic dimensions	4.4	Lift (h3)	h3	mm	710						
4.9		Height of tiller handle in drive position min./max.	h14	mm	1270				1230			
4.15		Height, lowered	h13	mm	85							
4.19		Overall length	l1	mm	1645				1580			
4.20		Length including fork shank	l2	mm	445				340			
4.21.1		Overall width	b1	mm	540							
4.22		Fork dimensions	s/ e/l	mm	50 x 163 x 1200							
4.25		Width across forks	b5	mm	540							
4.32		Ground clearance centre of wheelbase	m2	mm	19							
4.34.1		Aisle width (pallet 1000x1200 sideways)	Ast	mm	1690				1630			
4.34.2		Aisle width (pallet 800x1200 length)	Ast	mm	1890				1830			
4.35		Turning radius	Wa	mm	1540				1480			
Performance data		5.3	Lowering speed laden/unladen	m/s	0.07 / 0.05				0.15 / 0.09			
	6.4	Battery voltage/nominal capacity	V / Ah	12 / 65				-				
E-motor/ Electronics	6.5	Battery weight	kg	21				-				

- This data sheet according to VDI guideline 2198 only states the technical values of the standard truck. Different tyres, other masts, additional equipment etc. may result in different values.

- VDI no. 1.5: From a lift height of 470 mm, the capacity is reduced to 1,000 kg.

The German production facilities in  
Norderstedt, Moosburg and Landsberg  
are certified as well as our Genuine Parts  
Center in Kaltenkirchen. ISO 9001  
ISO 14001

Jungheinrich fork lift trucks meet  
European safety requirements. 

**JUNGHEINRICH**