

# Electric pedestrian pallet truck

**EJE 114i-118i** 

Lift height: 122 mm / Load capacity: 1400-1800 kg





### The efficient

### lithium-ion pallet truck.

#### Simple goods turnover over short distances.

The particularly efficient and manoeuvrable EJE 114i - 118i electric pedestrian pallet trucks with their integrated lithium-ion batteries offer the perfect combination of economic efficiency and robustness along with the flexibility of our highly efficient battery technology.

The integrated lithium-ion battery allows for an even more compact design leading to even greater manoeuvrability and lower weight. This makes them ideal for conventional applications on HGVs or in any other weight-sensitive and confined space.

In conjunction with the built-in charger for easy charging at any standard 230-V electricity outlet, lithium-ion technology offers a number of advantages: very long, maintenance-free battery life cycle as well as rapid and booster charging during breaks or downtime. This allows for 24/7 truck availability and flexible use in multi-shift operations.



#### Use your data to your advantage.

Utilise the data from your trucks to save time, energy and costs and increase efficiency. Our Telematics box (ex works) provides you with a free fleet management starter package that can be flexibly expanded with various hardware and software components.

### All benefits at a glance

- 24/7 availability due to built-in lithium-ion batteries
- Maximum manoeuvrability thanks to its very small front end compartment
- A lightweight in its class
- Ideal for use on HGV
- Built-in charger for quick charges at any standard 230-V electricity outlet

<sup>\*</sup> In accordance with our warranty terms - see website for details.

# Your Jungheinrich pallet truck

### for maximum customer benefits.



### **Efficiency**

# Maximum performance with the most efficient trucks.

Thanks to our integrated lithium-ion technology the result is a perfect combination of robustness and efficiency. Easier battery management and an integrated charger ensure flexible usage and high performance.

#### Integrated li-ion technology

- Built-in charger for fast charging at any 230-V electricity outlet, even during short breaks.
- No battery exchange or maintenance required.
- High degree of availability thanks to extremely short charging times.
- Saving costs due to longer service life and zero maintenance as compared to lead-acid batteries.
- No charging rooms and ventilation required as there is no build up of gas.



### Safety

# Best prerequisites for working safely.

With our lithium-ion technology you profit not only from high performance and zero maintenance but also from increased safety in your warehouse, as lithium-ion batteries do not build up gas as opposed to lead-acid batteries.

#### Safe handling and maintenance

- Maintenance-free 3-phase AC drive motor without carbon brushes.
- Easy access to all components through one-piece front cover secured by only two screws.
- Excellent protection against dust and humidity through IP 54 enclosure of controller and plugs.
- ProTracLink: Reduced support wheel wear when approaching ramps at an angle thanks to level equalisation. A mechanical link keeps both support wheels at the same height, ensuring no impact from the lower support wheel and therefore reducing damage.
- Increased safety due to lithiumion batteries that do not release any gases.

#### Crawl speed button

 Increased safety due to automatically reduced speed when manoeuvring with vertical tiller in confined spaces.



### **Individuality**

A forklift truck as individual as your business.

Innovative technologies, compact manoeuvrability and the low overall weight distinguish these models with lowest maintenance while performing highly, even in confined spaces.

#### Work ergonomically

- Tiller arm optimally adapted to the ergonomic needs of the operator.
- Clear colour coding and buttons with wear-resistant icons ensure intuitive operation.
- Grip position optimally adapted to the operator's hand posture.
- Easy accessibility of the crawl speed button when travelling with vertical tiller.
- Contactless sensor system with IP 65 protection rating guarantees high protection from breakdown.
- Rocker switch for consistent operation in all tiller positions.

#### Small, compact truck

- Extremely short front end length (l2 measurement) of only 416 mm, due to reduced battery compartment.
- Easy manoeuvring in very confined spaces.
- Överall weight including battery only 280 kg.

# **Overview**

# The right solution for your applications:

Name	Load capacity/load	Lift height (max.)	Travel speed unladen	Aisle width (pallet 800x1200 length)	Lift speed unladen
EJE 114i	1400 kg	122 mm	5 km/h	2058 mm	0.03 m/s
EJE 116i	1600 kg	122 mm	6 km/h	2058 mm	0.04 m/s
EJE 118i	1800 kg	122 mm	6 km/h	2058 mm	0.04 m/s

