



Hand pallet truck galvanised **AM G20**

Lift height: 122 mm / Load capacity: 2000 kg

JUNGHEINRICH

The hand pallet truck

with maximum corrosion protection.

Ideal for outdoor applications and humid surroundings.

The particularly compact and robust hand pallet trucks AM G20 are galvanised and are therefore suitable for outdoor applications or applications in humid surroundings such as whole sale markets or fruit growing farms.

Their special coating protects the AM G20 exceptionally well from damages caused by humidity. In combination with their construction out of hardened steel and the welded tiller mounting their durability is guaranteed.

Due to their optimised hydraulic and their bushed wheels, goods can be moved with remarkably less force. Additionally, the rounded forks and the protected entrance rollers make the pallet pick-up fast and easy.

Despite their extremely solid construction, the AM G20 remain manoeuvrable and agile. Their very short chassis length and the optionally shortened forks turn these hand pallet truck into the perfect support in confined spaces. Loading and unloading of HGV, for example, are no problem for the AM G20.



Approved
Jungheinrich quality

Proven quality by Jungheinrich

For decades, the Jungheinrich brand has been representing utmost reliability, premium-quality machines and comprehensive service whenever you need it. From hand pallet trucks to fully automated logistics systems – Jungheinrich delivers maximum quality.

All benefits at a glance

- Corrosion-resistant due to galvanised surfaces
- Optimised hydraulics for effortless handling
- Maintenance-free due to permanently lubricated connections
- Rounded fork tips and protected entrance rollers
- Extremely agile due to short chassis length

Your Jungheinrich hand pallet truck for maximum customer benefits.



Efficiency

Maximum performance with the most efficient trucks.

With the optimised control element – equally fitting for right- and left-handed operators – and the optimised hydraulic system nothing slows down the movement of goods in your warehouse.

Efficient Handling

- Smooth controls equally suitable for both left-handed and right-handed operators.
- Particularly sensitive and controlled lowering of goods with the special lowering valve.
- The optional fast lift (up to 120 kg) ensures that euro pallets can be lifted clear of the floor with just 3 pump strokes.
- The maximum lift height is achieved with only 5 pump strokes.
- Optimised hydraulic system for effortless pumping.
- Drawbar pull required is reduced by the bushes on the wheels.



Safety

Best prerequisites for working safely.

Durable material, a solid construction, and extreme protection from corrosion make the AM G20 a reliable and safe support in your warehouse.

Highest protection from corrosion

- Protection from humidity though galvanised surfaces.

Safe and manoeuvrable

- Safe and easy application, even in the most confined spaces, due to the short chassis length of only 373 mm.
- Embossed markings on the truck show the exact, secure pallet position required for crossways lifting.

Maximum stability and durability

- Strong forks and contoured shapes.
- Welded tiller mounting.
- Protected entry rollers.
- Hardened steel.



Individuality

A forklift truck as individual as your business.

With varying fork lengths, different braking systems and different wheel combinations, these hand pallet trucks can be adjusted to a variety of applications.

Quiet running

- Chromed bushes on the wheels and joints ensure particularly quiet running and an exceptionally long service life.
- Excellent smooth running even without lubrication of the connections.

Individual equipment

- Numerous fork lengths, wide range of width over forks.
- Different braking systems or special paint.
- Different wheel and roller combinations.

Overview

The right solution for your applications:

Name	Load capacity/load	Lift height (max.)	Aisle width (pallet 800x1200 length)
AM G20, 520x1,150, N-GN, SH	2000 kg	122 mm	1784 mm
AM G20, 520x1,150, N-BN, NH	2000 kg	122 mm	
AM G20, 520x1150, V-BV, NH	2000 kg	122 mm	1784 mm
AM G20, 520x950, N-GN, NH	2000 kg	122 mm	1784 mm
AM G20, 520x795, N-GN, NH	2000 kg	122 mm	1784 mm

The German production facilities in
Norderstedt, Moosburg and Landsberg
are certified as well as our Genuine Parts
Center in Kaltenkirchen.

ISO 9001
ISO 14001

 **JUNGHEINRICH**