



Elektrische reachtruck

ETV 314i - 325i

Hefhoogte: 10700-14000 mm / Capaciteit: 1400-2500 kg

The top view shows the side profile of the forklift truck. Key dimensions include:

- h_1 : Total height from the ground to the top of the mast.
- h_2 : Height from the ground to the top of the load center.
- h_3 : Height from the ground to the top of the mast.
- h_4 : Height from the ground to the top of the mast.
- h_5 : Height from the ground to the top of the mast.
- h_6 : Height from the ground to the top of the operator's seat.
- h_7 : Height from the ground to the top of the operator's seat.
- h_8 : Height from the ground to the top of the operator's seat.
- l_1 : Total length of the truck.
- l_2 : Length of the operator's compartment.
- l_3 : Length of the mast.
- l_4 : Length of the load center.
- l : Length of the load center.
- c : Distance from the front axle to the center of gravity of the load.
- Q : Weight of the load.
- s : Distance from the front axle to the center of gravity of the truck.
- m_2 : Mass of the load.
- x : Distance from the front axle to the center of gravity of the load.
- y : Distance from the front axle to the center of gravity of the truck.
- 220 : Width of the operator's compartment.
- α and β : Angles of the mast.

The bottom view shows the top profile of the truck. Key dimensions include:

- b_1 : Total width of the truck.
- b_2 : Width of the operator's compartment.
- b_3 : Width of the mast.
- b_4 : Width of the load center.
- b_5 : Width of the load center.
- b_6 : Width of the load center.
- b_7 : Width of the load center.
- b_8 : Width of the load center.
- b_9 : Width of the load center.
- b_{10} : Width of the load center.
- b_{11} : Width of the load center.
- a : Distance from the front axle to the center of gravity of the truck.
- $a/2$: Distance from the front axle to the center of gravity of the truck.
- Wa : Weight of the truck.
- Ast : Area of the truck.

ETV 314i - 325i

ETV 314i, ETV 316i	Heffing (h3)	Ingeschoven masthoogte (h1)	Vrije heffing (h2)	Uitgeschoven masthoogte (h4)	Neiging mast voorover/achterover	Neiging vorkenbord voorover/achterover
Mastneiging / Drievoudige mast DZ / koud vervormd	4550 mm	2050 mm	1396 mm	5204 mm	1 / 5 °	
	5000 mm	2200 mm	1546 mm	5654 mm	1 / 5 °	
	5300 mm	2300 mm	1646 mm	5954 mm	1 / 5 °	
	5600 mm	2400 mm	1746 mm	6254 mm	1 / 3 °	
	5900 mm	2500 mm	1846 mm	6554 mm	1 / 3 °	
	6200 mm	2600 mm	1946 mm	6854 mm	1 / 3 °	
	6500 mm	2700 mm	2046 mm	7154 mm	0,5 / 2 °	
	6800 mm	2800 mm	2146 mm	7454 mm	0,5 / 2 °	
	7100 mm	2900 mm	2246 mm	7754 mm	0,5 / 2 °	
	7310 mm	2970 mm	2316 mm	7964 mm	0,5 / 1 °	
	7400 mm	3000 mm	2346 mm	8054 mm	0,5 / 1 °	
	7700 mm	3100 mm	2446 mm	8354 mm	0,5 / 1 °	
	8000 mm	3200 mm	2546 mm	8654 mm	0,5 / 1 °	
	8300 mm	3300 mm	2646 mm	8954 mm	0,5 / 1 °	
	8420 mm	3340 mm	2686 mm	9074 mm	0,5 / 1 °	
	8720 mm	3440 mm	2786 mm	9374 mm	0,5 / 1 °	
	9020 mm	3540 mm	2886 mm	9674 mm	0,5 / 1 °	
Vorkneiging / Drievoudige mast DZ / koud vervormd	5000 mm	2200 mm	1546 mm	5654 mm		2 / 5 °
	5300 mm	2300 mm	1646 mm	5954 mm		2 / 5 °
	5600 mm	2400 mm	1746 mm	6254 mm		2 / 5 °
	5900 mm	2500 mm	1846 mm	6554 mm		2 / 5 °
	6200 mm	2600 mm	1946 mm	6854 mm		2 / 5 °
	6500 mm	2700 mm	2046 mm	7154 mm		2 / 5 °
	6800 mm	2800 mm	2146 mm	7454 mm		2 / 5 °
	7100 mm	2900 mm	2246 mm	7754 mm		2 / 5 °
	7400 mm	3000 mm	2346 mm	8054 mm		2 / 5 °
	7700 mm	3100 mm	2446 mm	8354 mm		2 / 5 °
	8000 mm	3200 mm	2546 mm	8654 mm		2 / 5 °
	8300 mm	3300 mm	2646 mm	8954 mm		2 / 5 °
	8420 mm	3340 mm	2686 mm	9074 mm		2 / 5 °
	8720 mm	3440 mm	2786 mm	9374 mm		2 / 5 °
	9020 mm	3540 mm	2886 mm	9674 mm		2 / 5 °
	9410 mm	3670 mm	3016 mm	10064 mm		2 / 5 °
	9920 mm	3840 mm	3186 mm	10574 mm		2 / 5 °
	10250 mm	3950 mm	3296 mm	10904 mm		2 / 5 °
	10520 mm	4040 mm	3386 mm	11174 mm		2 / 5 °
	10700 mm	4100 mm	3446 mm	11354 mm		2 / 5 °
ETV 318i, ETV 320i, ETV 325i	Heffing (h3)	Ingeschoven masthoogte (h1)	Vrije heffing (h2)	Uitgeschoven masthoogte (h4)	Neiging mast voorover/achterover	Neiging vorkenbord voorover/achterover
Mastneiging / Drievoudige mast DZ / koud vervormd	4250 mm	2050 mm	1320 mm	4980 mm	1 / 5 °	
	4700 mm	2200 mm	1470 mm	5430 mm	1 / 5 °	
	5000 mm	2300 mm	1570 mm	5730 mm	1 / 5 °	

	5300 mm	2400 mm	1670 mm	6030 mm	1 / 5 °	
	5600 mm	2500 mm	1770 mm	6330 mm	1 / 3 °	
	5900 mm	2600 mm	1870 mm	6630 mm	0,5 / 2 °	
	6200 mm	2700 mm	1970 mm	6930 mm	0,5 / 2 °	
	6500 mm	2800 mm	2070 mm	7230 mm	0,5 / 2 °	
	6800 mm	2900 mm	2170 mm	7530 mm	0,5 / 2 °	
	6950 mm	2950 mm	2220 mm	7680 mm	0,5 / 1 °	
	7400 mm	3100 mm	2370 mm	8130 mm	0,5 / 1 °	
	8000 mm	3300 mm	2570 mm	8730 mm	0,5 / 1 °	
	8420 mm	3440 mm	2710 mm	9150 mm	0,5 / 1 °	
	8720 mm	3540 mm	2810 mm	9450 mm	0,5 / 1 °	
	9110 mm	3670 mm	2940 mm	9840 mm	0,5 / 1 °	
Vorkneiging / Drievoudige mast DZ / koud vervormd	6200 mm	2700 mm	1970 mm	6930 mm	2 / 5 °	
	6500 mm	2800 mm	2070 mm	7230 mm	2 / 5 °	
	6800 mm	2900 mm	2170 mm	7530 mm	2 / 5 °	
	7400 mm	3100 mm	2370 mm	8130 mm	2 / 5 °	
	7700 mm	3200 mm	2470 mm	8430 mm	2 / 5 °	
	8000 mm	3300 mm	2570 mm	8730 mm	2 / 5 °	
	8420 mm	3440 mm	2710 mm	9150 mm	2 / 5 °	
	8720 mm	3540 mm	2810 mm	9450 mm	2 / 5 °	
	9110 mm	3670 mm	2940 mm	9840 mm	2 / 5 °	
	9620 mm	3840 mm	3110 mm	10350 mm	2 / 5 °	
	9950 mm	3950 mm	3220 mm	10680 mm	2 / 5 °	
	10220 mm	4100 mm	3370 mm	10950 mm	2 / 5 °	
	10520 mm	4200 mm	3470 mm	11250 mm	2 / 5 °	
	10700 mm	4260 mm	3530 mm	11430 mm	2 / 5 °	
	10880 mm	4320 mm	3590 mm	11610 mm	2 / 5 °	
	11120 mm	4400 mm	3670 mm	11850 mm	2 / 5 °	
	11510 mm	4530 mm	3800 mm	12240 mm	2 / 5 °	
	12020 mm	4700 mm	3970 mm	12750 mm	2 / 5 °	
	12530 mm	4870 mm	4140 mm	13260 mm	2 / 5 °	
ETV 320i, ETV 325i	Heffing (h3)	Ingeschoven masthoogte (h1)	Vrije heffing (h2)	Uitgeschoven masthoogte (h4)	Neiging mast voorover/achterover	Neiging vorkenbord voorover/achterover
Vorkneiging / Drievoudige mast DZ / koud vervormd	12830 mm	4970 mm	4240 mm	13560 mm	2 / 5 °	
	13000 mm	5026 mm	4296 mm	13728 mm	2 / 5 °	
	13505 mm	5425 mm	4695 mm	14235 mm	2 / 5 °	
	14000 mm	5590 mm	4860 mm	14730 mm	2 / 5 °	

VDI-tabel

Kenmerken	1.2	Typeaanduiding fabrikant			ETV 314i	ETV 316i	ETV 318i	ETV 320i	ETV 325i
	1.3	Aandrijving			Elektrisch				
	1.4	Bediening			Dwarsgeplaatste zitplaats				
	1.5	Capaciteit/last	Q	kg	1400	1600	1800	2000	2500
	1.6	Lastzwaartepuntafstand	c	mm	600				
	1.8	Lastafstand	x	mm	304	354	363	401	556
	1.8.1	Lastafstand, uitgeschoven mast		mm	205		230		
	1.9	Wielbasis	y	mm	1400	1450	1460	1508	1663
	Gewichten	2.1.1	Eigen gewicht (incl. accu)		kg	3270	3370	3560	3580
2.3		Aslast onbelast voor/achter		kg	2020 / 1250	2150 / 1220	2260 / 1300	2240 / 1340	2520 / 1360
2.4		Aslast vorken voor met last voor/achter		kg	750 / 3920	750 / 4220	700 / 4660	530 / 5050	560 / 5820
2.5		Aslast vorken achter met last voor/achter		kg	1710 / 2960	1860 / 3110	1960 / 3400	1960 / 3620	2370 / 4010
Wielen/chassis	3.1	Banden			Polyurethaan (PU)				
	3.2	Bandenmaat, voor			Ø 343 x 114			Ø343 x 114	Ø 343 x 140
	3.3	Bandenmaat, achter			Ø 285 x 100			Ø 355 x 106	Ø 355 x 135
	3.5	Wielen, aantal voor/achter (x = aangedreven)			1x / 2				
	3.7	Spoorbreedte, achter	b11	mm	1148		1172	1155	1184
Afmetingen	4.1	Neiging mast voorover/achterover	a/β	°	1 / 5				
	4.2	Ingeschoven masthoogte (h1)	h1	mm	2300		2400		
	4.3	Vrije heffing (h2)	h2	mm	1656		1670		
	4.4	Heffing (h3)	h3	mm	5300				
	4.5	Uitgeschoven masthoogte (h4)	h4	mm	5944		6030		
	4.7	Hoogte beschermend dak (cabine)	h6	mm	2091				
	4.8	Zithoogte / stahoogte	h7	mm	987				
	4.10	Hoogte wielarmen	h8	mm	282		283		284
	4.19	Totale lengte	l1	mm	2466		2467	2477	
	4.20	Lengte inclusief vorkrug	l2	mm	1316		1317	1327	
	4.21.1	Totale breedte	b1	mm	1270		1294	1290	1348
	4.21.2	Totale breedte	b2	mm	1270				
	4.22	Vorkafmetingen	s/ e/l	mm	40 x 120 x 1150			50 x 140 x 1150	
	4.23	Vorkenbord aansluitklasse			2B				
	4.24	Breedte vorkenbord	b3	mm	830				
	4.25	Maat over de vorken	b5	mm	335			356	
	4.25.1	Maat over de vorken (min./max.)	b5	mm	335 / 730			356 / 750	
	4.26	Maat tussen de wielarmen/laadruimte	b4	mm	940				
	4.28	Reachbaan		mm	506	586	565	629	784
	4.32	Bodemvrijheid midden wielbasis	m2	mm	80				
	4.34.2	Werkbreedte (pallet 800x1200 longitudinaal)	Ast	mm	2786	2790		2794	2883

	4.35	Draaicirkel	Wa	mm	1620	1670	1680	1728	1883
	4.37	Lengte over de wielarmen	L7	mm	1780	1830	1840	1920	2075
Prestaties	5.1	Rijsnelheid met last/onbelast		km/u	14 / 14				
	5.2	Hefsnelheid met last/onbelast		m/s	0,59 / 0,81		0,38 / 0,64		0,35 / 0,64
	5.3	Daalsnelheid met last/onbelast		m/s	0,55 / 0,55				
	5.4	Reachsnelheid met last/onbelast		m/s	0,2 / 0,2				
	5.7	Nominale helling met last/onbelast		%	9 / 13	8 / 12	7 / 11		
	5.8	Max. helling met last/onbelast		%	10 / 15		9 / 13	10 / 15	
	5.9	Acceleratietijd met last/onbelast		s	4,6 / 4,3		5,2 / 4,7	5,3 / 4,7	5,4 / 4,7
	5.10	Rem			elektrisch				
E-motor/elektronica	6.1	Rijmotor, vermogen S2 60 min		kW	9,5				
	6.2	Hefmotor, vermogen bij S3		kW	15,5				
	6.3	Accu volgens DIN 43531/35/36			Jungheinrich Li-ion				
	6.4	Accuspanning/nominaal vermogen		V	51,2				
	6.5	Accugewicht		kg	200			300	
Overig	8.1	Type rijregeling			Draaistroom				
	10.1	Werkdruk voor aanbouwapparaat		bar	150				
	10.2	Oliestroom voor aanbouwapparatuur		l/min	20				
	10.7	Geluidsdruk niveau volgens EN12053, stuurbuis		dB (A)	70				

- Dit typeblad volgens VDI-richtlijn 2198 noemt alleen de technische waarden van de standaardmachine. Afwijkende banden, andere hefmasten, extra systemen etc. kunnen resulteren in andere waarden.

De Duitse fabrieken in Norderstedt,
Moosburg en Landsberg zijn
gecertificeerd, evenals ons
onderdelenmagazijn in Kaltenkirchen.

ISO 9001
ISO 14001

Jungheinrich intern transport materieel
voldoet aan de Europese
veiligheidsvoorschriften.



 **JUNGHEINRICH**