



Electric pedestrian stacker with support arm lift

ERD 220i

Lift height: 1660-3760 mm / Load capacity: 2000 kg



The image contains two technical drawings of a truck chassis, labeled 'a' and 'b'.

Drawing 'a' (Side View): This drawing shows the side profile of the truck chassis. Key dimensions and labels include:

- Vertical dimensions: h_4 , h_6 , h_1 , h_{14} , 1271 , h_{13} , h_5 , h_2 , h_3 .
- Horizontal dimensions: l , c , x , y , l_1 , l_2 , m_2 , $a/2$.
- Force: Q (downward arrow).
- Ground line: Indicated by a hatched area at the bottom.
- Text: "632/529 komfort/kompakt" is written below the chassis.

Drawing 'b' (Top View): This drawing shows the top-down view of the truck chassis. Key dimensions and labels include:

- Vertical dimensions: b_1 , b_{10} , b_5 , b_{11} , b_{12} .
- Horizontal dimensions: $a/2$, l_6 .
- Angles: α (at the front left corner) and α_{st} (at the rear).
- Other labels: Wa (pointing to the front grille area) and e (distance between rear axles).

ERD 220i

ERD 220i	Lift (h3)	Retracted mast height (h1)	Free lift (h2)	Extended mast height (h4)
Duplex mast ZT	1660 mm	1330 mm	100 mm	2125 mm
	2010 mm	1505 mm	100 mm	2475 mm
	2100 mm	1550 mm	100 mm	2565 mm
	2560 mm	1780 mm	100 mm	3025 mm
	2900 mm	1950 mm	100 mm	3365 mm
Triplex mast DZ	3070 mm	1500 mm	990 mm	3580 mm
	3760 mm	1730 mm	1220 mm	4270 mm

VDI table

Characteristic	1.1	Manufacturer (abbreviated description)		Jungheinrich
	1.2	Manufacturer's type designation		ERD 220i
	1.3	Drive type		electric
	1.4	Operation		Tiller
	1.5	Load capacity/load	Q kg	2000
	1.5.1	Rated capacity/load with mast lift	Q kg	1000
	1.5.2	Rated capacity/load with support arm lift	Q kg	2000
	1.6	Load centre distance	c mm	600
	1.8	Load distance, centre of drive axle to fork	x mm	959
	1.9	Wheelbase	y mm	1495
Weights	2.1.1	Service weight (incl. battery)	kg	1055
	2.2	Axle load laden front/rear	kg	1245 / 1810
	2.3	Axle load unladen front/rear	kg	835 / 220
Wheels/chassis	3.1	Tyres		Polyurethane (PU)
	3.2	Tyre size, front		ø 230x77
	3.3	Tyre size, rear		ø 85x95
	3.4	Additional wheels		ø 140x57
	3.5	Wheels, number front/back (x=driven)		1x +2
	3.6	Tread width, front	b10 mm	512
	3.7	Tread width, rear	b11 mm	385
Basic dimensions	4.2	Retracted mast height (h1)	h1 mm	1505
	4.3	Free lift (h2)	h2 mm	100
	4.4	Lift (h3)	h3 mm	2010
	4.5	Extended mast height (h4)	h4 mm	2475
	4.6	Initial lift	h5 mm	120
	4.9	Height of tiller handle in drive position min./max.	h14 mm	1215 / 1275
	4.15	Height, lowered	h13 mm	94
	4.19	Total length	l1 mm	2358
	4.20	Length including fork shank	l2 mm	1168
	4.21.1	total width	b1 mm	770
	4.22	Fork dimensions	s/e/l mm	56 x 185 x 1190
	4.25	Width across forks	b5 mm	570
	4.32	Ground clearance centre of wheelbase	m2 mm	18
	4.34.1	Aisle width (pallet 1000x1200 sideways)	Ast mm	2564
	4.34.2	Aisle width (pallet 800x1200 length)	Ast mm	2574
	4.35	Turning radius	Wa mm	2133

Performance data	5.1	Travel speed laden/unladen (Efficiency drivePLUS)	km/h	9 / 12.5 9 / 14
	5.2	Lift speed laden/unladen	m/s	0.21 / 0.37
	5.3	Lowering speed laden/unladen	m/s	0.49 / 0.44
	5.7	Gradeability laden/unladen	%	8 / 16
	5.8	Max. gradeability laden/unladen	%	8 / 16
	5.10	Service brake		generative
Electric motor/electronics	6.1	Drive motor, performance S2 60 min (Efficiency drivePLUS)	kW	2.8 3.2
	6.2	Lift motor, performance with S3	kW	2.2
	6.3	Battery according to DIN 43531/35/36		Jungheinrich Li-ion
	6.4	Battery voltage/nominal capacity	V / Ah	24 / 260
	6.5	Battery weight	kg	100
	6.6.1	Energy consumption according to EN cycle (Efficiency PLUS)	kWh/h	0.6 0.65
	6.6.2	CO2 equivalent as per EN 16796 (Efficiency PLUS)	kg/h	0.3 0.4
	6.7	Throughput (Efficiency PLUS)	t/h	100 106
	6.8	Turnover efficiency according to VDI 2198 (Efficiency PLUS)	t/kWh	106 105
	6.8.1	Energy consumption with max. throughput (Efficiency PLUS)	kWh/h	0.94 1.01
Other	10.7	Sound pressure level according to EN12053	dB (A)	67.1
- This data sheet according to VDI guideline 2198 only states the technical values of the standard truck. Different tyres, other masts, additional equipment etc. may result in different values.				

The values in the table apply for the fixed stand-on platform, integrated M battery compartment, ZT2010 mast without overhead guard, raised support arm lift.

Entry height for stand-on platform: 202 / 214 mm (stand-on platform standard / stand-on platform suspension adjustable).

Ground clearance at end of stand-on platform: 117 / 98 mm (stand-on platform standard / stand-on platform compact).

An overhead guard is optionally available and compulsory for masts with $h_3 > 2,300$ mm. (VDI no. 4.7 height of overhead guard: $h_6 = 2,300$ mm: VDI no. 4.8 stand height with unladen stand-on platform: $h_7 = 2,037 / 2,025$ mm (stand-on platform standard / stand-on platform suspension adjustable)).

- VDI no. 1.5: in double-decker mode: mast lift max. 1 t / overall load max. 2 t.
- VDI no. 1.8: lowered support arm lift: $x + 46$ mm. With fork length 1,150 mm: $x - 40$ mm. With DZ mast: $x - 18$ mm.
- VDI no. 1.9: lowered support arm lift: $y + 46$ mm. With fork length 1,150 mm: $y - 40$ mm.
- VDI no. 4.19: with fork length 1,150 mm: $l_1 - 40$ mm. with compact stand-on platform: $l_1 - 103$ mm. With DZ mast: $l_1 + 18$ mm.
- VDI no. 4.20: with compact stand-on platform: $l_2 - 103$ mm. With DZ mast: $l_2 + 18$ mm.
- VDI no. 4.34.1: with fork length 1,150 mm: aisle width - 40 mm. With compact stand-on platform: aisle width - 103 mm. With DZ mast: aisle width + 18 mm.
- VDI no. 4.34.2: with fork length 1,150 mm: aisle width - 40 mm. With compact stand-on platform: aisle width - 103 mm. With DZ mast: aisle width + 10 mm.
- VDI no. 4.35: lowered support arm lift: $W_a + 46$ mm. with fork length 1,150 mm: $W_a - 40$ mm. With compact stand-on platform: $W_a - 103$ mm.

The German production facilities in
Norderstedt, Moosburg and Landsberg
are certified as well as our Genuine Parts
Center in Kaltenkirchen.

ISO 9001
ISO 14001

Jungheinrich fork lift trucks meet
European safety requirements.



 **JUNGHEINRICH**