



Electric pedestrian stacker with support arm lift

EJC 212z-220z

Lift height: 2400-6000 mm / Load capacity: 1200-2000 kg



EJC 212z-220z



EJC 212z-220z

EJC 212z	Lift (h3)	Retracted mast height (h1)	Free lift (h2)	Extended mast height (h4)
Duplex mast ZT	2500 mm	1750 mm	100 mm	2975 mm
	2700 mm	1850 mm	100 mm	3175 mm
	2900 mm	1950 mm	100 mm	3375 mm
	3200 mm	2100 mm	100 mm	3675 mm
	3600 mm	2300 mm	100 mm	4075 mm
	4100 mm	2550 mm	100 mm	4575 mm
	4300 mm	2650 mm	100 mm	4775 mm
Duplex mast ZZ	2500 mm	1700 mm	1225 mm	2975 mm
	2900 mm	1900 mm	1425 mm	3375 mm
	3200 mm	2050 mm	1575 mm	3675 mm
	3600 mm	2250 mm	1775 mm	4075 mm
	4100 mm	2500 mm	2025 mm	4575 mm
	4300 mm	2600 mm	2125 mm	4775 mm
Triplex mast DZ	4090 mm	1845 mm	1338 mm	4597 mm
	4300 mm	1915 mm	1408 mm	4807 mm
	4700 mm	2050 mm	1543 mm	5207 mm
EJC 214z	Lift (h3)	Retracted mast height (h1)	Free lift (h2)	Extended mast height (h4)
Duplex mast ZT	2500 mm	1750 mm	100 mm	2975 mm
	2700 mm	1850 mm	100 mm	3175 mm
	2900 mm	1950 mm	100 mm	3375 mm
	3200 mm	2100 mm	100 mm	3675 mm
	3600 mm	2300 mm	100 mm	4075 mm
	4100 mm	2550 mm	100 mm	4575 mm
	4300 mm	2650 mm	100 mm	4775 mm
	4500 mm	2750 mm	100 mm	4975 mm
Duplex mast ZZ	2500 mm	1700 mm	1225 mm	2975 mm
	2900 mm	1900 mm	1425 mm	3375 mm

	3200 mm	2050 mm	1575 mm	3675 mm	
	3600 mm	2250 mm	1775 mm	4075 mm	
	4100 mm	2500 mm	2025 mm	4575 mm	
	4300 mm	2600 mm	2125 mm	4775 mm	
Triplex mast DZ	4090 mm	1830 mm	1341 mm	4579 mm	
	4300 mm	1900 mm	1411 mm	4789 mm	
	4690 mm	2030 mm	1541 mm	5179 mm	
	5350 mm	2250 mm	1761 mm	5839 mm	
EJC 214z, EJC 216z		Lift (h3)	Retracted mast height (h1)	Free lift (h2)	Extended mast height (h4)
Triplex mast DZ	6000 mm	2500 mm	1968 mm	6532 mm	
EJC 216z		Lift (h3)	Retracted mast height (h1)	Free lift (h2)	Extended mast height (h4)
Duplex mast ZT	2400 mm	1750 mm	100 mm	2925 mm	
	2600 mm	1850 mm	100 mm	3125 mm	
	2800 mm	1950 mm	100 mm	3325 mm	
	3100 mm	2100 mm	100 mm	3625 mm	
	3500 mm	2300 mm	100 mm	4025 mm	
	3800 mm	2450 mm	100 mm	4325 mm	
	4000 mm	2550 mm	100 mm	4525 mm	
	4200 mm	2650 mm	100 mm	4725 mm	
	4400 mm	2750 mm	100 mm	4925 mm	
	Duplex mast ZZ	2400 mm	1700 mm	1175 mm	2925 mm
2800 mm		1900 mm	1375 mm	3325 mm	
3100 mm		2050 mm	1525 mm	3625 mm	
3500 mm		2250 mm	1725 mm	4025 mm	
4000 mm		2500 mm	1975 mm	4525 mm	
4200 mm		2600 mm	2075 mm	4725 mm	
Triplex mast DZ	3990 mm	1830 mm	1298 mm	4522 mm	
	4200 mm	1900 mm	1368 mm	4732 mm	
	4590 mm	2030 mm	1498 mm	5122 mm	

	5250 mm	2250 mm	1718 mm	5782 mm
EJC 220z	Lift (h3)	Retracted mast height (h1)	Free lift (h2)	Extended mast height (h4)
Duplex mast ZT	2540 mm	1950 mm	100 mm	3195 mm
	2840 mm	2100 mm	100 mm	3495 mm
	3540 mm	2450 mm	100 mm	4195 mm
Duplex mast ZZ	2540 mm	1900 mm	1245 mm	3195 mm
	2840 mm	2050 mm	1395 mm	3495 mm
	3540 mm	2400 mm	1745 mm	4195 mm
Triplex mast DZ	3750 mm	1900 mm	1218 mm	4432 mm
	4200 mm	2050 mm	1368 mm	4882 mm
	4800 mm	2250 mm	1568 mm	5482 mm

VDI table

Characteristic	1.1	Manufacturer (abbreviated description)			Jungheinrich				
	1.2	Manufacturer's type designation			EJC 212z	EJC 214z	EJC 216z	EJC 220z	
	1.3	Drive type			electric				
	1.4	Operation			Pedestrian				
	1.5	Load capacity/load		Q	kg	1200	1400	1600	2000
	1.5.1	Rated capacity/load with mast lift		Q	kg	1200	1400	1600	2000
	1.5.2	Rated capacity/load with support arm lift		Q	kg	2000			
	1.6	Load centre distance		c	mm	600			
	1.8	Load distance, centre of drive axle to fork		x	mm	910			
	1.9	Wheelbase		y	mm	1571	1592		
Weights	2.1.1	Service weight (incl. battery)			kg	1180	1240	1260	1300
	2.2	Axle load laden front/rear			kg	1105 / 1275	1180 / 1460	1250 / 1610	1300 / 2000
	2.3	Axle load unladen front/rear			kg	840 / 340	880 / 360	900 / 360	910 / 390
Wheels/chassis	3.1	Tyres				Polyurethane (PU)			
	3.2	Tyre size, front				Ø 230 x 70			
	3.3	Tyre size, rear				Ø 85 x 95			Ø 85 x 75
	3.4	Additional wheels				Ø 140 x 54			
	3.5	Wheels, number front/back (x=driven)				1x + 1 / 2			1x + 1 / 4
	3.6	Tread width, front		b10	mm	507			
	3.7	Tread width, rear		b11	mm	385			
Basic dimensions	4.2	Retracted mast height (h1)		h1	mm	1950			2100
	4.3	Free lift (h2)		h2	mm	100			
	4.4	Lift (h3)		h3	mm	2900		2800	2840
	4.5	Extended mast height (h4)		h4	mm	3375		3325	3495
	4.6	Initial lift		h5	mm	122			
	4.9	Height of tiller handle in drive position min./max.		h14	mm	850 / 1305			
	4.15	Height, lowered		h13	mm	90			
	4.19	Total length		l1	mm	1981	2002		
	4.20	Length including fork shank		l2	mm	831	852		
	4.21.1	total width		b1	mm	800			
	4.22	Fork dimensions		s/ e/l	mm	56 x 185 x 1150			
	4.25	Width across forks		b5	mm	570			
	4.32	Ground clearance centre of wheelbase		m2	mm	18			
	4.34.1	Aisle width (pallet 1000x1200 sideways)		Ast	mm	2217	2238		
	4.34.2	Aisle width (pallet 800x1200 length)		Ast	mm	2267	2288		
	4.35	Turning radius		Wa	mm	1777	1798		

Performance data	5.1	Travel speed laden/unladen	km/h	6 / 6			
	5.2	Lift speed laden/unladen	m/s	0.2 / 0.4	0.16 / 0.3	0.15 / 0.3	0.11 / 0.34
	5.3	Lowering speed laden/unladen	m/s	0.45 / 0.35			0.5 / 0.35
	5.8	Max. gradeability laden/unladen	%	8 / 16		7 / 16	5 / 16
Electric motor/electronics	6.1	Drive motor, performance S2 60 min	kW	1.6			
	6.2	Lift motor, performance with S3	kW	3			
	6.3	Battery according to DIN 43531/35/36		no			
	6.4	Battery voltage/nominal capacity	V / Ah	24 / 375			
	6.5	Battery weight	kg	300			288
	6.6	Energy consumption according to VDI cycle	kWh/h	1.05	1.18	1.32	0
	6.6.1	Energy consumption according to EN cycle	kWh/h	0.77	0.83	0.91	1.08
	6.6.2	CO2 equivalent as per EN 16796	kg/h	0.4		0.5	0.6
Other	8.1	Type of drive control		AC			
	10.7	Sound pressure level according to EN12053	dB (A)	63			
- This data sheet according to VDI guideline 2198 only states the technical values of the standard truck. Different tyres, other masts, additional equipment etc. may result in different values.							

The values in the table apply for the LX-LBE battery compartment; mast ZT2800 / 2840 / 2900 mm, raised support arms. The battery compartments have no influence on the truck dimensions.

- VDI no. 1.8 with EJC 212z / 214z / 216z: with DZ mast: x - 42 mm; with lowered support arms: x + 54 mm.
- VDI no. 1.8 with EJC 220z: with DZ mast: x - 71 mm; with lowered support arms: x + 54 mm.
- VDI no. 1.9: with lowered support arms: x + 54 mm.
- VDI no. 3.3: tandem: Ø 85 x 75 mm.
- VDI no. 4.19 with EJC 212z / 214z / 216z: with DZ mast: l1 + 42 mm.
- VDI no. 4.19 with EJC 220z: with DZ mast: l1 + 71 mm.
- VDI no. 4.20 with EJC 212z / 214z / 216z: with DZ mast: l2 + 42 mm.
- VDI no. 4.20 with EJC 220z: with DZ mast: l2 + 71 mm.
- VDI no. 4.34.1 with EJC 212z / 214z / 216z: diagonal as per VDI: aisle width + 367 mm. with DZ mast: aisle width + 42 mm.
- VDI no. 4.34.1 with EJC 220z: diagonal as per VDI: aisle width + 367 mm. with DZ mast: aisle width + 71 mm.
- VDI no. 4.34.2 with EJC 212z / 214z / 216z: diagonal as per VDI: aisle width + 204 mm. with DZ mast: aisle width + 42 mm.
- VDI no. 4.34.2 with EJC 220z: diagonal as per VDI: aisle width + 204 mm. with DZ mast: aisle width + 71 mm.
- VDI no. 4.35: with lowered support arms: + 54 mm.
- VDI no. 5.3: with ZZ / DZ mast: the lowering speed in free lift is below the specified values.
- VDI no. 5.8: the values in the table relate to the rated load (1.5). With maximum load in the support arm lift (1.5.2): max. gradeability laden = 5%.

The German production facilities in
Norderstedt, Moosburg and Landsberg
are certified as well as our Genuine Parts
Center in Kaltenkirchen.

ISO 9001
ISO 14001

Jungheinrich fork lift trucks meet
European safety requirements.



 **JUNGHEINRICH**