



Electric pedestrian pallet truck

AME 20

Lift height: 115 mm / Load capacity: 2000 kg

Powerful and lightweight.

Unstoppable in shops, in production, and in and around the lorry.

The Jungheinrich AME 20 pallet trucks demonstrate their strength particularly where space is tight or where service weights play a decisive role. They offer impressive manoeuvrability, load capacity and reliability – even under challenging logistical conditions.

With a capacity of 2,000 kg, a compact design and low service weights, they are ideal for daily pallet transport and for use as on-board trucks. The one-handed operation on both sides ensures simple and intuitive control – a clear advantage in everyday work.

The AME 20 trucks are also well positioned in terms of energy efficiency and availability: they have modern lithium-ion technology for energy-saving operation, offer flexible interim charging via the built-in charger and have a maintenance-free drive motor.

Safety is, of course, a top priority: a reinforced steel construction ensures stability, while protected support wheels and high driving and cornering stability significantly reduce the risk to people, trucks and cargo alike.

All benefits at a glance

- Powerful mid-range electric pedestrian pallet truck, ideal for use as an on-board truck.
- Intuitive and safe operation, as well as high driving and cornering stability.
- Reinforced steel construction and protected support wheels for robustness and safety.
- Optimal availability thanks to lithium-ion battery and built-in charger.
- Durable and low-maintenance – manufactured in proven Jungheinrich quality.

Your Jungheinrich pallet truck for maximum customer benefits.



Efficiency

Maximum performance with the most efficient trucks.

Powerful in deployment, robust and economical in everyday operation.

Ideal for daily work tasks

- Low energy consumption
- Maintenance-free drive motor
- Lightweight, manoeuvrable and compact
- Improved robustness and capacity

Excellent energy efficiency

- Cost-efficient thanks to longer life cycles
- Flexible deployment thanks to booster charging of the lithium-ion battery
- Easy charging at any socket via the integrated built-in charger
- Automatic shutdown when not in use protects your budget and the environment

Innovative lithium-ion technology

- Save time and money thanks to maintenance-free operation
- High truck availability through rapid and booster charging
- Up to three times the lifespan compared with lead-acid batteries
- Reliable operation thanks to high-quality battery management system



Safety

Best conditions for working safely.

Intuitive handling and well-thought-out protection for people, machines and goods.

Convenient and safe to use

- Greater stability thanks to two sprung support wheels positioned next to the drive wheel
- Safe and precise manoeuvring thanks to good coordination of software and chassis
- 8% gradeability
- Fully integrated, protected support wheels
- Slow travel button for manoeuvring with the tiller in a vertical position
- Two travel programs for adjusted speeds (2.5 km/h and 5.5 km/h)
- Precise control of fork entry depth prevents damage to pallets and trucks
- Easy transverse pallet lifting thanks to tandem fork rollers plus protected entry rollers



Individuality

A forklift truck as individual as your business.

With the robust Jungheinrich AME electric pedestrian pallet truck, you can transport goods flexibly and reliably both indoors and outdoors.

Universal and versatile

- Tiller head with one-handed operation on both sides
- Convenient charging via built-in charger
- Truck status visible via highly visible LED strips
- Easy access via PIN code
- All control instruments, including display, are installed and clearly arranged in the tiller
- Fork marking at 800 mm for precise transverse lifting of pallets
- Different fork lengths available
- Storage compartment on the battery lid

Overview

The right solution for your applications:

Name	Load capacity/load	Lift height (max.)	Travel speed unladen	Aisle width (pallet 800x1200 length)	Lift speed unladen
AME 15 (540x800)	2000 kg	115 mm	5.5 km/h	1958 mm	0.04 m/s
AME 15 (540x1000)	2000 kg	115 mm	5.5 km/h	2003 mm	0.04 m/s
AME 15 (540x1150)	2000 kg	115 mm	5.5 km/h	2060 mm	0.04 m/s
AME 15 (540x1150)	2000 kg	115 mm	5.5 km/h	2060 mm	0.04 m/s
AME 15 (685x1000)	2000 kg	115 mm	5.5 km/h	2090 mm	0.04 m/s
AME 15 (685x1150)	2000 kg	115 mm	5.5 km/h	2003 mm	0.04 m/s
AME 15 (685x1150)	2000 kg	115 mm	5.5 km/h	2060 mm	0.04 m/s
AME 15 (685x1150)	2000 kg	115 mm	5.5 km/h	2060 mm	0.04 m/s

The German production facilities in
Norderstedt, Moosburg and Landsberg
are certified as well as our Genuine Parts
Center in Kaltenkirchen.

ISO 9001
ISO 14001

 **JUNGHEINRICH**