



## Electric pedestrian pallet truck

**AME 15**

Lift height: 115 mm / Load capacity: 1500 kg

# Powerful and lightweight.

Unstoppable in shops, in production, and in and around the lorry.

Jungheinrich AME 15 pallet trucks are the optimal solution for tight spaces and weight-sensitive work environments. With their high manoeuvrability and robust performance, they easily master demanding logistics processes.

The combination of compact dimensions and low service weights makes them the first choice for daily in-house pallet transport and for use as on-board trucks. Their intuitive usability and one-handed operation on both sides make every working task easier.

Thanks to their high driving and cornering stability, the Jungheinrich AME 15 pedestrian pallet trucks operate with maximum safety during everyday tasks. A reinforced steel construction and protected support wheels make them extremely robust and durable.

Their high efficiency is also a key advantage: the low energy consumption based on the latest lithium-ion technology, the option of booster charging and the maintenance-free drive motor ensure high availability in daily operation.

## All benefits at a glance

- Powerful mid-range electric pedestrian pallet truck, ideal for use as an on-board truck.
- Intuitive and safe operation, as well as high driving and cornering stability.
- Optimised robustness thanks to reinforced steel construction and protected support wheels.
- Lithium-ion battery and low energy consumption for high availability.
- Proven Jungheinrich quality with durable components.

# Your Jungheinrich pallet truck for maximum customer benefits.



## Efficiency

Maximum performance with the most efficient trucks.

Maintenance free, robust and economical in everyday operation.

### Ideal for daily work tasks

- Low energy consumption
- Maintenance-free drive motor
- Lightweight, manoeuvrable and compact
- Improved robustness and performance

### Optimal energy efficiency

- Efficient charging processes without expensive charging infrastructure
- Cost-efficient thanks to longer life cycles
- Flexible deployment thanks to booster charging of the lithium-ion battery
- Easy charging at a socket using the supplied charger
- Automatic shutdown when not in use saves costs and protects the environment

### Modern lithium-ion technology

- Maintenance-free battery saves both time and costs
- Rapid and booster charging ensures high truck availability.
- Up to three times the lifespan compared with lead-acid batteries
- Reliable operation thanks to high-quality battery management system



## Safety

Best conditions for working safely.

Easy handling and well-thought-out protection for people, machines and goods.

### Intuitive and easy to operate

- Two sprung support wheels positioned to the side of the drive wheel increase stability
- Safe and precise manoeuvring thanks to well-coordinated software and chassis
- High gradeability: 8%
- Fully integrated, protected support wheels
- Slow travel button for manoeuvring
- Two travel programs for adjusted speeds (2.5 km/h and 5.5 km/h)
- Precise control of fork entry depth prevents damage to pallets and trucks
- Tandem fork rollers plus protected entry rollers for comfortable pallet transverse lifting



## Individuality

A forklift truck as individual as your business.

With the robust Jungheinrich AME 15 electric pedestrian pallet truck, you can transport goods flexibly and reliably both indoors and outdoors.

### Universal and versatile

- Tiller head with one-handed operation on both sides
- Truck status visible via highly visible LED strips
- Easy access via PIN code
- All control instruments, including display, are installed and clearly arranged in the tiller
- Fork marking at 800 mm for precise transverse lifting of pallets
- Different fork lengths available

# Overview

The right solution for your applications:

Name	Load capacity/load	Lift height (max.)	Travel speed unladen	Aisle width (pallet 800x1200 length)	Lift speed unladen
AME 15 (540x800)	1500 kg	115 mm	5.5 km/h	1958 mm	0.04 m/s
AME 15 (540x1000)	1500 kg	115 mm	5.5 km/h	2003 mm	0.04 m/s
AME 15 (540x1150)	1500 kg	115 mm	5.5 km/h	2060 mm	0.04 m/s
AME 15 (540x1150)	1500 kg	115 mm	5.5 km/h	2060 mm	0.04 m/s
AME 15 (685x1000)	1500 kg	115 mm	5.5 km/h	2003 mm	0.04 m/s
AME 15 (685x1150)	1500 kg	115 mm	5.5 km/h	2060 mm	0.04 m/s
AME 15 (685x1150)	1500 kg	115 mm	5.5 km/h	2060 mm	0.04 m/s

The German production facilities in  
Norderstedt, Moosburg and Landsberg  
are certified as well as our Genuine Parts  
Center in Kaltenkirchen.

ISO 9001  
ISO 14001

 **JUNGHEINRICH**