



Medium/high level order picker **EKS 110**

Lift height: 1000-2800 mm / Load capacity: 1000 kg

Abbildung zeigt EKS 110 Z 280 ZZ

Abbildung zeigt EKS 110 L 100 E

Abbildung zeigt EKS 110 Z 280 ZZ

Abbildung zeigt EKS 110 L 100 E

VDI table

Characteristic	1.1	Manufacturer (abbreviated description)		Jungheinrich							
	1.2	Manufacturer's type designation		EKS 110							
	1.3	Drive		Electric							
	1.4	Operation		Order pickers							
	1.5	Load capacity/load	Q kg	1000							
	1.6	Load centre distance	c mm	600							
	1.8	Load distance, centre of drive axle to fork	x mm	143	180	148	185				
	1.9	Wheelbase	y mm	1330	1385	1330	1385				
Weights	2.1.1	Service weight (incl. battery)	kg	1661	1785	1813	2268	1763	1907	1953	2390
	2.2	Axle load laden front/rear	kg	491 / 2170	516 / 2269	506 / 2307	762 / 2506	489 / 2274	508 / 2399	504 / 2449	754 / 2636
	2.3	Axle load unladen front/rear	kg	1053 / 608	1093 / 692	1084 / 729	1336 / 932	1062 / 701	1083 / 824	1079 / 874	1328 / 1062
Wheels/suspension system	3.1	Tyres		Vulkollan ®							
	3.2	Tyre size, front		ø 230 x 80							
	3.3	Tyre size, rear		ø 150 x 130							
	3.5	Wheels, number front/back (x=driven)		1x / 2							
	3.7	Tread width, rear	b11 mm	630	720	630	720				
Basic dimensions	4.2	Retracted mast height (h1)	h1 mm	1650	2260	2560	2250	1650	2260	2560	2250
	4.4	Lift (h3)	h3 mm	1000	1600	1900	2800	1000	1600	1900	2800
	4.5	Extended mast height (h4)	h4 mm	2650	3830	4130	5030	2650	3830	4130	5030
	4.7	Height of overhead guard (cab)	h6 mm	-	2230			-	2230		
	4.8.1	Stand height	h7 mm	200							
	4.11	Additional lift	h9 mm	-				800			
	4.14	Stand height, elevated	h12 mm	1200	1800	2100	3000	1200	1800	2100	3000
	4.15	Height, lowered	h13 mm	80							
	4.19	total length	l1 mm	2890			2980	2895			2985
	4.20	Length including fork shank	l2 mm	1690			1780	1695			1785
	4.21.1	total width	b1 mm	810			900	810			900
	4.22	Fork dimensions	s/ e/l mm	60 x 160 x 1200							
	4.25	Width across forks	b5 mm	540							
	4.26	Width between support arms/ loading areas	b4 mm	430			520	430			520
	4.27	Width over guide rollers	b6 mm	970			1060	970			1060
	4.31	Ground clearance laden under mast	m1 mm	35							
	4.34.1	Aisle width (pallet 1000x1200 sideways)	Ast mm	3039			3127	3039			3127

	4.34.2	Aisle width (pallet 800x1200 length)	Ast	mm	3149			3240	3154			3245
	4.35	Turning radius	Wa	mm	1548			1603	1548			1603
Performance data	5.1	Travel speed laden/unladen (Efficiency drivePLUS)	km/h		9 / 10 10 / 13	9 / 9 10 / 12	9 / 9 9.5 / 12	9 / 9 9 / 11	9 / 10 10 / 13	9 / 9 10 / 12	9 / 9 9.5 / 12	9 / 9 9 / 11
	5.2	Lift speed laden/unladen	m/s		0.19 / 0.26	0.15 / 0.2		0.23 / 0.31	0.19 / 0.26	0.15 / 0.2		0.23 / 0.31
	5.3	Lowering speed laden/unladen	m/s		0.24 / 0.24	0.23 / 0.22		0.28 / 0.26	0.24 / 0.24	0.23 / 0.22		0.28 / 0.26
	5.7	Gradeability laden/unladen	%		5 / 10							
	5.10	Service brake			generative							
	5.11	Parking brake			Electromagnetic spring-loaded brake system							
E-motor/Electronics	6.1	Drive motor, performance S2 60 min	kW		3.2							
	6.2	Lift motor, performance with S3	kW		3			6	3			6
	6.3	Battery according to DIN 43531/35/36			DIN 43535 B							
	6.4	Battery voltage/nominal capacity	V / Ah		24 / 620							
	6.5	Battery weight	kg		480							
	6.6.1	Energy consumption according to EN cycle	kWh/h		0.42							
Other	8.1	Type of drive control			AC							
	10.5	Steering version			Electric power steering							
	10.7	Sound level as per EN12053, operator's ear	dB (A)		61							
- This data sheet according to VDI guideline 2198 only states the technical values of the standard truck. Different tyres, other masts, additional equipment etc. may result in different values.												

- 4.2: L100E with overhead guard 2,230 mm
- 4.5: L100E with overhead guard 3,230 mm
- 4.7: L100E and Z100E overhead guard optional

The German production facilities in
Norderstedt, Moosburg and Landsberg
are certified as well as our Genuine Parts
Center in Kaltenkirchen.

ISO 9001
ISO 14001

 **JUNGHEINRICH**