





Medium/high level order picker


EKS 210

Lift height: 2800-4750 mm / Load capacity: 1000 kg

EKS 210







EKS 210

EKS 210 Z, EKS 210 L, EKS 210 O	Lift (h3)	Retracted mast height (h1)	Extended mast height (h4)
Duplex mast ZT	2800 mm	2325 mm	5170 mm
	3500 mm	2550 mm	5870 mm
	4250 mm	2950 mm	6620 mm
	4750 mm	3200 mm	7120 mm

E-motor/Electronics	6.1	Drive motor, performance S2 60 min	kW		3.2
	6.2	Lift motor, performance with S3	kW		8
	6.3	Battery according to DIN 43531/35/36			5 PzS 775
	6.4	Battery voltage/nominal capacity	V / Ah		24 / 775
	6.5	Battery weight	kg		600
Other	8.1	Type of drive control			AC drive control system
	10.5	Steering version			electric
	10.7	Sound level as per EN12053, operator's ear	dB (A)		60

- This data sheet according to VDI guideline 2198 only states the technical values of the standard truck. Different tyres, other masts, additional equipment etc. may result in different values.

The German production facilities in
Norderstedt, Moosburg and Landsberg
are certified as well as our Genuine Parts
Center in Kaltenkirchen.

 **JUNGHEINRICH**