




## **Electric pedestrian stacker** **ERC 214bi-216bi**

Lift height: 2400-6000 mm / Load capacity: 1400-1600 kg



ERC 214bi-216bi



## ERC 214bi-216bi

| ERC 214bi            | Lift (h3) | Retracted mast height (h1) | Free lift (h2) | Extended mast height (h4) |
|----------------------|-----------|----------------------------|----------------|---------------------------|
| Duplex mast ZT       | 2500 mm   | 1800 mm                    | 100 mm         | 3025 mm                   |
|                      | 2760 mm   | 1930 mm                    | 100 mm         | 3285 mm                   |
|                      | 2900 mm   | 2000 mm                    | 100 mm         | 3425 mm                   |
|                      | 3160 mm   | 2130 mm                    | 100 mm         | 3685 mm                   |
|                      | 3600 mm   | 2350 mm                    | 100 mm         | 4125 mm                   |
|                      | 4100 mm   | 2600 mm                    | 100 mm         | 4625 mm                   |
|                      | 4300 mm   | 2700 mm                    | 100 mm         | 4825 mm                   |
| Triplex mast DZ      | 4090 mm   | 1880 mm                    | 1348 mm        | 4622 mm                   |
|                      | 4300 mm   | 1950 mm                    | 1418 mm        | 4832 mm                   |
|                      | 4690 mm   | 2080 mm                    | 1548 mm        | 5222 mm                   |
|                      | 5350 mm   | 2300 mm                    | 1768 mm        | 5882 mm                   |
| ERC 214bi, ERC 216bi | Lift (h3) | Retracted mast height (h1) | Free lift (h2) | Extended mast height (h4) |
| Triplex mast DZ      | 6000 mm   | 2550 mm                    | 1968 mm        | 6582 mm                   |
| ERC 216bi            | Lift (h3) | Retracted mast height (h1) | Free lift (h2) | Extended mast height (h4) |
| Duplex mast ZT       | 2400 mm   | 1800 mm                    | 100 mm         | 2975 mm                   |
|                      | 2660 mm   | 1930 mm                    | 100 mm         | 3235 mm                   |
|                      | 2800 mm   | 2000 mm                    | 100 mm         | 3375 mm                   |
|                      | 3060 mm   | 2130 mm                    | 100 mm         | 3635 mm                   |
|                      | 3500 mm   | 2350 mm                    | 100 mm         | 4075 mm                   |
|                      | 4000 mm   | 2600 mm                    | 100 mm         | 4575 mm                   |
|                      | 4200 mm   | 2700 mm                    | 100 mm         | 4775 mm                   |
| Triplex mast DZ      | 3990 mm   | 1880 mm                    | 1298 mm        | 4572 mm                   |
|                      | 4200 mm   | 1950 mm                    | 1368 mm        | 4782 mm                   |
|                      | 4590 mm   | 2080 mm                    | 1498 mm        | 5172 mm                   |
|                      | 5250 mm   | 2300 mm                    | 1718 mm        | 5832 mm                   |

## VDI table

|                  |        |                                                     |          |                   |             |
|------------------|--------|-----------------------------------------------------|----------|-------------------|-------------|
| Characteristic   | 1.1    | Manufacturer (abbreviated description)              |          | Jungheinrich      |             |
|                  | 1.2    | Manufacturer's type designation                     |          | ERC 214bi         | ERC 216bi   |
|                  | 1.3    | Drive type                                          |          | electric          |             |
|                  | 1.4    | Operation                                           |          | Operator platform |             |
|                  | 1.5    | Load capacity/load                                  | Q kg     | 1400              | 1600        |
|                  | 1.6    | Load centre distance                                | c mm     | 600               |             |
|                  | 1.8    | Load distance, centre of drive axle to fork         | x mm     | 681               |             |
|                  | 1.9    | Wheelbase                                           | y mm     | 1324              |             |
| Weights          | 2.1.1  | Service weight (incl. battery)                      | kg       | 1500              | 1510        |
|                  | 2.2    | Axle load laden front/rear                          | kg       | 1215 / 1685       | 1230 / 1880 |
|                  | 2.3    | Axle load unladen front/rear                        | kg       | 1145 / 355        | 1150 / 360  |
| Wheels/chassis   | 3.1    | Tyres                                               |          | Polyurethane (PU) |             |
|                  | 3.2    | Tyre size, front                                    |          | Ø 230 x 77        |             |
|                  | 3.3    | Tyre size, rear                                     |          | Ø 85 x 75         |             |
|                  | 3.4    | Additional wheels                                   |          | Ø 140 x 57        |             |
|                  | 3.5    | Wheels, number front/back (x=driven)                |          | 1x + 1 / 4        |             |
|                  | 3.6    | Tread width, front                                  | b10 mm   | 535               |             |
|                  | 3.7    | Tread width, rear                                   | b11 mm   | 1000              |             |
|                  | 3.7.1  | 2. Tread width, rear                                | mm       | 1170              |             |
|                  | 3.7.2  | 3. Tread width, rear                                | mm       | 1370              |             |
| Basic dimensions | 4.2    | Retracted mast height (h1)                          | h1 mm    | 2300              |             |
|                  | 4.3    | Free lift (h2)                                      | h2 mm    | 1768              | 1718        |
|                  | 4.4    | Lift (h3)                                           | h3 mm    | 5350              | 5250        |
|                  | 4.5    | Extended mast height (h4)                           | h4 mm    | 5882              | 5832        |
|                  | 4.7    | Height of overhead guard (cab)                      | h6 mm    | 2300              |             |
|                  | 4.9    | Height of tiller handle in drive position min./max. | h14 mm   | 1185 / 1245       |             |
|                  | 4.19   | Total length                                        | l1 mm    | 2425              |             |
|                  | 4.20   | Length including fork shank                         | l2 mm    | 1274              |             |
|                  | 4.21.1 | total width                                         | b1 mm    | 1100              |             |
|                  | 4.22   | Fork dimensions                                     | s/e/l mm | 40 x 100 x 1150   |             |
|                  | 4.24   | Fork carriage width                                 | b3 mm    | 800               |             |
|                  | 4.32   | Ground clearance centre of wheelbase                | m2 mm    | 50                |             |
|                  | 4.34.1 | Aisle width (pallet 1000x1200 sideways)             | Ast mm   | 2632              |             |
|                  | 4.34.2 | Aisle width (pallet 800x1200 length)                | Ast mm   | 2682              |             |
|                  | 4.35   | Turning radius                                      | Wa mm    | 1963              |             |
| Performance data | 5.1    | Travel speed laden/unladen                          | km/h     | 9 / 12            |             |
|                  | 5.2    | Lift speed laden/unladen                            | m/s      | 0.19 / 0.35       |             |
|                  | 5.3    | Lowering speed laden/unladen                        | m/s      | 0.43 / 0.49       |             |
|                  | 5.8    | Max. gradeability laden/unladen                     | %        | 8 / 16            |             |
|                  | 5.10   | Service brake                                       |          | generative        |             |

|                                                                                                                                                                                                   |       |                                           |        |                     |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------|-------------------------------------------|--------|---------------------|
| Electric motor/electronics                                                                                                                                                                        | 6.1   | Drive motor, performance S2 60 min        | kW     | 3.2                 |
|                                                                                                                                                                                                   | 6.2   | Lift motor, performance with S3           | kW     | 3                   |
|                                                                                                                                                                                                   | 6.3   | Battery according to DIN 43531/35/36      |        | Jungheinrich Li-ion |
|                                                                                                                                                                                                   | 6.4   | Battery voltage/nominal capacity          | V / Ah | 24 / 260            |
|                                                                                                                                                                                                   | 6.5   | Battery weight                            | kg     | 98                  |
|                                                                                                                                                                                                   | 6.6   | Energy consumption according to VDI cycle | kWh/h  | 0                   |
|                                                                                                                                                                                                   | 6.6.1 | Energy consumption according to EN cycle  | kWh/h  | 0.96                |
|                                                                                                                                                                                                   | 6.6.2 | CO2 equivalent as per EN 16796            | kg/h   | 0.5                 |
|                                                                                                                                                                                                   | 6.7   | Throughput                                | t/h    | 83                  |
|                                                                                                                                                                                                   | 6.8.1 | Energy consumption with max. throughput   | kWh/h  | 2.31                |
| Other                                                                                                                                                                                             | 8.1   | Type of drive control                     |        | AC                  |
|                                                                                                                                                                                                   | 10.7  | Sound pressure level according to EN12053 | dB (A) | 68                  |
| - This data sheet according to VDI guideline 2198 only states the technical values of the standard truck. Different tyres, other masts, additional equipment etc. may result in different values. |       |                                           |        |                     |

The values in the table apply for the 260-Ah Li-ion battery, DZ 5350 / DZ 5250 mast, fork length 1,150 mm, with overhead guard, without bumper.

- VDI no. 1.8: with duplex telescopic mast:  $x + 32$  mm
- VDI no. 4.19: with duplex telescopic mast:  $l_1 - 32$  mm
- VDI no. 4.20: with duplex telescopic mast:  $l_2 - 32$  mm
- VDI no. 4.21: depending on tread width: 1,100 / 1,270 / 1,470 mm
- VDI no. 4.24: available fork carrier widths: ISO 2A 800 / 975 mm
- VDI no. 4.34.1: diagonal as per VDI, depending on tread width: aisle width + 211 / + 211 / + 273 mm; with duplex telescopic mast: aisle width - 32 mm
- VDI no. 4.34.2: diagonal as per VDI, depending on tread width: aisle width + 136 / + 136 / + 223 mm; with duplex telescopic mast: aisle width - 32 mm
- VDI no. 6.2: with S3 = 11%
- VDI no. 6.5: with 130-Ah battery = 76 kg

The German production facilities in  
Norderstedt, Moosburg and Landsberg  
are certified as well as our Genuine Parts  
Center in Kaltenkirchen.

ISO 9001  
ISO 14001

Jungheinrich fork lift trucks meet  
European safety requirements.



 **JUNGHEINRICH**