




## **Electric tow tractor** **EZS 570-5100**

**Towing capacity: 7000-10000 kg**



[illegible]

EZS 580, technical drawing, data sheet



# VDI table

|                          |        |                                        |     |                    |             |             |             |             |
|--------------------------|--------|----------------------------------------|-----|--------------------|-------------|-------------|-------------|-------------|
| Characteristic           | 1.1    | Manufacturer (abbreviated description) |     | Jungheinrich       |             |             |             |             |
|                          | 1.2    | Manufacturer's type designation        |     | EZS 5              |             |             |             |             |
|                          | 1.3    | Drive                                  |     | Electric           |             |             |             |             |
|                          | 1.4    | Operation                              |     | Seat               |             |             |             |             |
|                          | 1.5.3  | Towing capacity                        | Q   | kg                 | 7000        | 8000        | 9000        | 10000       |
|                          | 1.7    | Rated drawbar pull                     |     | N                  | 1400        | 1600        | 1800        | 2000        |
|                          | 1.9    | Wheelbase                              | y   | mm                 | 1035        |             |             | 1250        |
| Weights                  | 2.1.1  | Service weight (incl. battery)         |     | kg                 | 1260        | 1320        | 1410        | 1825        |
|                          | 2.3    | Axle load unladen front/rear           |     | kg                 | 580 / 680   | 580 / 740   | 620 / 790   | 880 / 945   |
| Wheels/suspension system | 3.1    | Tyres                                  |     | Super-elastic (SE) |             |             |             |             |
|                          | 3.2    | Tyre size, front                       |     | 4.00-8             | 16x6-8      |             | 16x6-8      |             |
|                          | 3.3    | Tyre size, rear                        |     | 4.00-8             |             |             |             |             |
|                          | 3.5    | Wheels, number front/back (x=driven)   |     | 1 / 2x             |             |             |             |             |
|                          | 3.6    | Tread width, front                     | b10 | mm                 | 0           |             |             |             |
|                          | 3.7    | Tread width, rear                      | b11 | mm                 | 870         |             |             |             |
| Basic dimensions         | 4.7    | Height of overhead guard (cab)         | h6  | mm                 | 2150        |             |             | 2140        |
|                          | 4.8    | Seat height/stand height               | h7  | mm                 | 1040        |             |             |             |
|                          | 4.12   | Coupling height                        | h10 | mm                 | 265         |             |             |             |
|                          | 4.12.1 | 2. Coupling height                     |     | mm                 | 330         |             |             |             |
|                          | 4.12.2 | 3. Coupling height                     |     | mm                 | 395         |             |             |             |
|                          | 4.13   | Loading height, unladen                |     | mm                 | 650         | 640         |             |             |
|                          | 4.16   | Loading area length                    | l3  | mm                 | 400         |             |             |             |
|                          | 4.17   | Overhang length                        |     | mm                 | 375         |             |             |             |
|                          | 4.18   | Loading area width                     | b9  | mm                 | 795         |             |             |             |
|                          | 4.19   | total length                           | l1  | mm                 | 1828        |             |             | 2048        |
|                          | 4.21.1 | total width                            | b1  | mm                 | 996         |             |             |             |
|                          | 4.32   | Ground clearance centre of wheelbase   | m2  | mm                 | 160         | 130         |             |             |
|                          | 4.35   | Turning radius                         | Wa  | mm                 | 1652        |             |             | 1866        |
|                          | 4.36   | Smallest pivot point distance          | b13 | mm                 | 600         |             |             | 665         |
| Performance data         | 5.1    | Travel speed laden/unladen             |     | km/h               | 9 / 18      | 8.5 / 18    |             | 7.5 / 18    |
|                          | 5.5    | Drawbar pull laden                     |     | N                  | 1400        | 1600        | 1800        | 2000        |
|                          | 5.6    | Max. drawbar pull laden/unladen        |     | N                  | 5500 / 5500 | 6500 / 6500 | 7500 / 7500 | 7600 / 7600 |
|                          | 5.10   | Service brake                          |     |                    | electric    |             |             |             |

|                     |       |                                           |        |            |     |      |          |
|---------------------|-------|-------------------------------------------|--------|------------|-----|------|----------|
| E-motor/Electronics | 6.1   | Drive motor, performance S2 60 min        | kW     | 4.5        |     |      |          |
|                     | 6.4   | Battery voltage/nominal capacity          | V / Ah | 48 / 375   |     |      | 48 / 625 |
|                     | 6.5   | Battery weight                            | kg     | 575        |     |      | 860      |
|                     | 6.6   | Energy consumption according to VDI cycle | kWh/h  | 0          |     |      |          |
|                     | 6.6.1 | Energy consumption according to EN cycle  | kWh/h  | 1.33       | 1.5 | 1.67 | 1.84     |
|                     | 6.6.2 | CO2 equivalent as per EN 16796            | kg/h   | 0.7        | 0.8 | 0.9  | 1        |
| Other               | 8.1   | Type of drive control                     |        | Impulse/AC |     |      |          |
|                     | 10.7  | Sound pressure level according to EN12053 | dB (A) | 62         |     |      |          |

- This data sheet according to VDI guideline 2198 only states the technical values of the standard truck. Different tyres, other masts, additional equipment etc. may result in different values.

The German production facilities in  
Norderstedt, Moosburg and Landsberg  
are certified as well as our Genuine Parts  
Center in Kaltenkirchen.

 **JUNGHEINRICH**