



Hand pallet truck

AMX I15 / I15 e / I15 p / I15 ep

Lift height: 710 mm / Load capacity: 1500 kg

JUNGHEINRICH

The versatile stainless steel scissor lift hand pallet truck.

Corrosion and acid-resistant for strict hygiene requirements.

Our versatile scissor lift hand pallet trucks AMX I17/I15e in the stainless steel version are the ideal vehicles for all applications in aggressive environments with highest hygiene requirements.

The inox steel used for these models is extremely corrosion resistant against humidity, acids and salts, therefore the trucks are a perfect fit in the food industry as well as the pharmaceutical and chemical industry. When these models were designed, the possibility to clean them quickly was of utmost importance. You will not find any hard to reach niches or hollow spaces.

To guarantee food safety all used lubricants are food grade. The closed fork tips offer additional protection against slashes from the tyres.

Naturally, this series also offers the flexibility of our scissor lift hand pallet trucks: as hand pallet truck, lift table or work bench.



Approved
Jungheinrich quality

Proven quality by Jungheinrich

For decades, the Jungheinrich brand has been representing utmost reliability, premium-quality machines and comprehensive service whenever you need it. From hand pallet trucks to fully automated logistics systems – Jungheinrich delivers maximum quality.

All benefits at a glance

- Completely corrosion, salt, and acid-resistant
- Available with manual or electronic hydraulic system
- Protected hydraulics prevents ingress of water
- Easy to clean construction
- Food grade lubricants (class H1/H2)

Your Jungheinrich hand pallet truck for maximum customer benefits.



Efficiency

Maximum performance with the most efficient trucks.

With the fast lift, the manual hydraulic or the built-in charger – fast and efficient movement of goods is always at the centre.

Efficient Handling

- Smooth controls equally suitable for both left-handed and right-handed operators.
- Particularly sensitive and controlled lowering of goods with the special lowering valve.
- The optional fast lift (up to 120 kg) ensures that euro pallets can be lifted clear of the floor with just 3 pump strokes.
- The maximum lift height is achieved with only 5 pump strokes.
- Optimised hydraulic system for effortless pumping.
- Drawbar pull required is reduced by the bushes on the wheels.

Built-in charger (AMX I15e)

- Standard built-in rectifier.
- Charging of maintenance-free batteries on every 230 V electricity outlet.
- Maintenance-free 65-Ah battery.



Safety

Best prerequisites for working safely.

Special environments need special safety measures – guaranteed through high-end materials and optimised hydraulic.

Highest protection from corrosion


- Acid resistant stainless steel chassis.
- Protection from humidity through galvanised surfaces.

Safe and manoeuvrable

- Safe and easy application, even in the most confined spaces, due to the short chassis length of only 340 mm.
- Additional pillars for reliable safety for a lifted height up to 800 mm.
- Better stability while taking strain off the ground with standard tandem rolls.
- Easy pallet pick-up due to skid bar at fork tips.
- Pump unit with integrated tank and lowering valve for sensitive lowering through manual lever.
- Pressure limiting valve to protect hydraulics from overloading.

Maximum stability and durability

- Strong forks and contoured shapes.
- Welded tiller mounting.
- Protected entry rollers.
- Hardened steel.



Individuality

A forklift truck as individual as your business.

These stainless steel hand pallet trucks meet your individual requirements on safety and hygiene without problems. Designed for the daily use in extreme environments.

Hygiene to the last detail

- Robust and torsion free closed fork tips protect the cargo from splashing from the ground.
- Hollow spaces that are either completely closed or easy to reach allow for effective cleaning without hideouts for bacteria.
- Grease nipples on all moving parts.
- Food grade lubricants (class H1 and H2).

Individual equipment

- Lifting and lowering: Manual or electric hydraulic with 1.2 kW lift motor.
- Polyurethane tyres for a comfortable and smooth run.
- Nylon tyres for robustness and high chemical resistance.

Overview

The right solution for your applications:

Name	Load capacity/load	Lift height (max.)	Aisle width (pallet 800x1200 length)
AMX l15e, 540x1200, N-BN	1500 kg	710 mm	1890 mm
AMX l15e, 540x1200, V-BV	1500 kg	710 mm	1890 mm
AMX l15ep, 540x1200, N-BN	1500 kg	710 mm	1890 mm
AMX l15ep, 540x1200, V-BV	1500 kg	710 mm	1890 mm
AMX l15, 540x1200, N-BN	1500 kg	710 mm	1830 mm
AMX l15, 540x1200, V-BV	1500 kg	710 mm	1830 mm
AMX l15p, 540x1200, N-BN,	1500 kg	710 mm	1830 mm
AMX l15p, 540x1200, V-BV	1500 kg	710 mm	1830 mm

The German production facilities in
Norderstedt, Moosburg and Landsberg
are certified as well as our Genuine Parts
Center in Kaltenkirchen.

ISO 9001
ISO 14001

Jungheinrich fork lift trucks meet
European safety requirements.



 **JUNGHEINRICH**