



Hand pallet truck

AM 22 SH / 22 NH

Lift height: 122 mm / Load capacity: 2200 kg

 JUNGHEINRICH

AM 22 SH / 22 NH



VDI table

Characteristic	1.1	Manufacturer (abbreviated description)		Other (OEM)							
	1.2	Manufacturer's type designation		AM 22 NH							
	1.3	Drive type		Manual							
	1.4	Operation		Manual							
	1.5	Load capacity/load	Q kg	2200					1500	1000	
	1.6	Load centre distance	c mm	300	400	500	600	700	800	900	
	1.9	Wheelbase	y mm	560	755	910	1110	1320	1560	1860	
Weights	2.1	Netto weight	kg	50	52	56	60	61	70	82	
Wheels/chassis	3.1	Tyres		C-BV							
	3.2	Tyre size, front		Ø 170x50							
	3.3	Tyre size, rear		Ø 82x96							
	3.5	Wheels, number front/back (x=driven)		2/4							
	3.6	Tread width, front	b10 mm	109							
	3.7	Tread width, rear	b11 mm	370							
Basic dimensions	4.4	Lift (h3)	h3 mm	122							
	4.9	Height of tiller handle in drive position min./max.	h14 mm	359 / 1237							
	4.14	Stand height, elevated	h12 mm	205							
	4.15	Height, lowered	h13 mm	83							
	4.19	Total length	l1 mm	973	1168	1323	1523	1733	1973	2273	
	4.20	Length including fork shank	l2 mm	373							
	4.21.1	total width	b1 mm	520							
	4.22	Fork dimensions	s/e/l mm	53 x 150 x 600	53 x 150 x 795	53 x 150 x 950	53 x 150 x 1150	53 x 150 x 1207	53 x 150 x 1360	53 x 150 x 1600	53 x 150 x 1900
	4.25	Width across forks	b5 mm	520							
	4.32	Ground clearance centre of wheelbase	m2 mm	30							
	4.34.1	Aisle width (pallet 1000×1200 sideways)	Ast mm	1584			1734		1933	2173	2473
	4.34.2	Aisle width (pallet 800x1200 length)	Ast mm	1784				1933		2173	2473
	4.35	Turning radius	Wa mm	724	919	1074	1274	1484	1724	2024	
Performance data	5.3	Lowering speed laden/unladen	m/s	0.09 / 0.02							
- This data sheet according to VDI guideline 2198 only states the technical values of the standard truck. Different tyres, other masts, additional equipment etc. may result in different values.											

Characteristic	1.1	Manufacturer (abbreviated description)			Other (OEM)						
	1.2	Manufacturer's type designation			AM 22 NH					AM 22 SH	
	1.3	Drive type			Manual						
	1.4	Operation			Manual						
	1.5	Load capacity/load	Q	kg	500	2200					
	1.6	Load centre distance	c	mm	1200	600	550	500	600	500	300
	1.9	Wheelbase	y	mm	2360	1110	1014	910	1110	910	560
Weights	2.1	Netto weight		kg	90	63	62	59	63	59	50
Wheels/chassis	3.1	Tyres			C-BV	C-GV	V-GV	C-BN	C-BV	V-BV	N-GN
	3.2	Tyre size, front			Ø 170x50						
	3.3	Tyre size, rear			Ø 82x96						
	3.5	Wheels, number front/back (x=driven)			2/4	2/2	2/4			2/2	
	3.6	Tread width, front	b10	mm	109						
	3.7	Tread width, rear	b11	mm	370						
Basic dimensions	4.4	Lift (h3)	h3	mm	122						
	4.9	Height of tiller handle in drive position min./max.	h14	mm	359 / 1237						
	4.14	Stand height, elevated	h12	mm	205						
	4.15	Height, lowered	h13	mm	83						
	4.19	Total length	l1	mm	2773	1523	1427	1323	1523	1323	973
	4.20	Length including fork shank	l2	mm	373						
	4.21.1	total width	b1	mm	520	680				520	
	4.22	Fork dimensions	s/ e/l	mm	53 x 150 x 2400	53 x 150 x 1150	53 x 150 x 1054	53 x 150 x 950	53 x 150 x 1150	53 x 150 x 950	53 x 150 x 600
	4.25	Width across forks	b5	mm	520	680				520	
	4.32	Ground clearance centre of wheelbase	m2	mm	30						
	4.34.1	Aisle width (pallet 1000×1200 sideways)	Ast	mm	2973	1734	1627	1584	1734	1584	
	4.34.2	Aisle width (pallet 800x1200 length)	Ast	mm	2973	1784					
4.35	Turning radius	Wa	mm	2524	1274	1178	1074	1274	1074	724	
Performance data	5.3	Lowering speed laden/unladen		m/s	0.09 / 0.02						
- This data sheet according to VDI guideline 2198 only states the technical values of the standard truck. Different tyres, other masts, additional equipment etc. may result in different values.											

Characteristic	1.1	Manufacturer (abbreviated description)		Other (OEM)					
	1.2	Manufacturer's type designation		AM 22 SH					
	1.3	Drive type		Manual					
	1.4	Operation		Manual					
	1.5	Load capacity/load	Q kg	2200					
	1.6	Load centre distance	c mm	600	500	600	500	600	500
	1.9	Wheelbase	y mm	1110	910	1110	910	1110	910
Weights	2.1	Netto weight	kg	60	59	63	59	64	59
Wheels/chassis	3.1	Tyres		V-BV	N-GN		C-GV		C-BV
	3.2	Tyre size, front		Ø 170x50					
	3.3	Tyre size, rear		Ø 82x96					
	3.5	Wheels, number front/back (x=driven)		2/4	2/2				2/4
	3.6	Tread width, front	b10 mm	109					
	3.7	Tread width, rear	b11 mm	370					
Basic dimensions	4.4	Lift (h3)	h3 mm	122					
	4.9	Height of tiller handle in drive position min./max.	h14 mm	359 / 1237					
	4.14	Stand height, elevated	h12 mm	205					
	4.15	Height, lowered	h13 mm	83					
	4.19	Total length	l1 mm	1523	1323	1523	1323	1523	1323
	4.20	Length including fork shank	l2 mm	373					
	4.21.1	total width	b1 mm	520	680				
	4.22	Fork dimensions	s/ e/l mm	53 x 150 x 1150	53 x 150 x 950	53 x 150 x 1150	53 x 150 x 950	53 x 150 x 1207	53 x 150 x 950
	4.25	Width across forks	b5 mm	520	680				
	4.32	Ground clearance centre of wheelbase	m2 mm	30					
	4.34.1	Aisle width (pallet 1000×1200 sideways)	Ast mm	1734	1584	1734	1584	1573	1584
	4.34.2	Aisle width (pallet 800x1200 length)	Ast mm	1784				1773	1784
	4.35	Turning radius	Wa mm	1274	1074	1274	1074	724	1074
Performance data	5.3	Lowering speed laden/unladen	m/s	0.09 / 0.02					
- This data sheet according to VDI guideline 2198 only states the technical values of the standard truck. Different tyres, other masts, additional equipment etc. may result in different values.									

Note. The tables do not represent all tyre variants. Not all tyre variants are available for all fork lengths.

Available tyres:

Steering wheels: N = nylon, C = rubber, V = polyurethane.

Load rollers: GN = single nylon, GV = single polyurethane, BN = tandem nylon, BV = tandem polyurethane.

The German production facilities in
Norderstedt, Moosburg and Landsberg are
certified as well as our Genuine Parts
Center in Kaltenkirchen.

ISO 9001
ISO 14001

Jungheinrich fork lift trucks meet European
safety requirements.



 **JUNGHEINRICH**