



Elektrisk dragtruck

EZS 570-5100

Dragkraft: 7000-10000 kg



The figure consists of two technical drawings of a vehicle, likely a small truck or van, used for dimensioning purposes.


The top drawing is a side view of the vehicle. It shows the profile of the cab and the front end. Key dimensions labeled include:

- 1420 : Overall height from the ground to the top of the cab roof.
- h_6 : Height from the ground to the top of the steering wheel.
- h_7 : Height from the ground to the top of the windshield frame.
- h_{11} : Height from the ground to the top of the rear door.
- h_{10a} , h_{10b} , h_{10c} : Heights from the ground to different points on the rear door handle area.
- m_2 : A vertical distance from the ground to a point on the front suspension.
- y : Horizontal distance from the front axle centerline to the rear door.
- l_5 : Horizontal distance from the rear door to the rear bumper.
- l_1 : Total horizontal length from the front axle centerline to the rear bumper.

The bottom drawing is a top-down view of the vehicle. It shows the interior layout, including the steering wheel, dashboard, and seats. Key dimensions labeled include:

- b_1 : Overall width of the vehicle.
- Wa : An angle indicating the orientation of the front end relative to the side view.
- b_{13} : Width of the rear door opening.
- b_9 : Width of the rear door panel.
- b_{11} : Total width of the rear section, including the door and side panels.
- l_3 : Horizontal distance from the front axle centerline to the rear door.

EZS 580, teknisk ritning, typblad



VDI bord

Specifikation	1.1	Tillverkare (kort namn)		Jungheinrich				
	1.2	Tillverkarens typbeteckning		EZS 570	EZS 580	EZS 590	EZS 5100 XL	
	1.3	Drivning		Elektrisk				
	1.4	Manövrering		Säte				
	1.5.3	Dragkraft	Q kg	7000	8000	9000	10000	
	1.7	Nominell dragkraft	N	1400	1600	1800	2000	
	1.9	Hjulbas	y mm	1035				1250
Vikter	2.1.1	Egenvikt (inkl. batteri)	kg	1260	1320	1410	1825	
	2.3	Axelbelastning utan last fram/bak	kg	580 / 680	580 / 740	620 / 790	880 / 945	
Hjul/chassi	3.1	Däck		Halvmassivt (SE)				
	3.2	Däckstorlek, fram		4.00-8	16x6-8		16x6-8	
	3.3	Däckstorlek, bak		4.00-8				
	3.5	Hjul, nummer fram / bak (x = driven)		1 / 2x				
	3.6	Spårvidd, fram	b10 mm	0				
	3.7	Spårvidd, bak	b11 mm	870				
Grundmått	4.7	Höjd av skyddande tak (hytt)	h6 mm	2150				2140
	4.8	Säteshöjd / ståhöjd	h7 mm	1040				
	4.12	Dragkrok höjd	h10 mm	265				
	4.12.1	2. Dragkrok höjd	mm	330				
	4.12.2	3. Dragkrok höjd	mm	395				
	4.13	Lasthöjd utan last	mm	650	640			
	4.16	Lastytans längd	l3 mm	400				
	4.17	Överhängslängd	mm	375				
	4.18	Lastytans bredd	b9 mm	795				
	4.19	Total längd	l1 mm	1828				2048
	4.21.1	Total bredd	b1 mm	996				
	4.32	Markfrigång mitten av hjulbasen	m2 mm	160	130			
	4.35	Vändradie	Wa mm	1652				1866
	4.36	Minsta vridpunktsavstånd	b13 mm	600				665
Prestanda	5.1	Körhastighet med/utan last	km/h	9 / 18	8,5 / 18		7,5 / 18	
	5.5	Dragkraft med/utan last	N	1400 / 1400	1600 / 1600	1800 / 1800	2000 / 2000	
	5.6	Max. dragkraft med/utan last	N	5500 / 5500	6500 / 6500	7500 / 7500	7600 / 7600	
	5.10	Driftbroms		elektrisk				

Elektrisk motor / Elektronik	6.1	Drivmotor, prestanda S2 60 min	kW	4,5			
	6.4	Batterispänning/nom. kapacitet	V / Ah	48 / 375			48 / 625
	6.5	Batterivikt	kg	575			860
	6.6	Energiförbrukning enligt VDI-cykel	kWh/h	0			
	6.6.1	Energiförbrukning enligt EN-cykel	kWh/h	1,33	1,5	1,67	1,84
	6.6.2	CO2-ekvivalent enligt EN ISO 23308	kg/h0	0,7	0,8	0,9	1
Övrigt	8.1	Typ av körkontroll		Impuls/AC			
	10.7	Ljudtrycksnivå enligt EN12053	dB (A)	62			

- Detta typblad är enligt VDI-riktlinje 2198 och anger endast de tekniska värdena för standardtrucken. Avvikande däcktyper, andra stativ, tillsatsaggregat osv. kan ge andra värden.

Jungheinrich Svenska AB

Huvudkontor:

Starrvägen 16

232 61 ARLÖV

Telefon 040 - 690 46 00

Telefax 040 - 690 46 99

kundkontakt@jungheinrich.se

www.jungheinrich.se

I Tyskland är truckfabrikerna i Norderstedt,
Moosburg och Landsberg samt vårt
reservdelscenter i Kaltenkirchen
certifierade.

ISO 9001
ISO 14001

Jungheinrichs truckar uppfyller de
europeiska säkerhetskraven.



**JUNGHEINRICH**