





Hand pallet truck with scales

AMW 22 / 22p

Lift height: 122 mm / Load capacity: 2200 kg

 JUNGHEINRICH



VDI table

Characteristic	1.1	Manufacturer (abbreviated description)		AMW 22				Other (OEM)			
	1.2	Manufacturer's type designation		AMW 22				AMW 22p			
	1.3	Drive type						Manual			
	1.4	Operation						Manual			
	1.5	Load capacity/load	Q kg					2200			
	1.6	Load centre distance	c mm					600			
	1.9	Wheelbase	y mm					1110			
Weights	2.1	Netto weight	kg	99				102			
	2.2	Axle load laden front/rear	kg					578 / 1721			
	2.3	Axle load unladen front/rear	kg					61 / 38			
Wheels/chassis	3.1	Tyres		C-BV	V-GV	C-GV	V-BV	C-GV	C-BV	V-GV	V-BV
	3.2	Tyre size, front		Ø 170x50	Ø 170 x 50		Ø 170x50	Ø 170 x 50	Ø 170x50	Ø 170 x 50	Ø 170x50
	3.3	Tyre size, rear		Ø 82x96	Ø 82 x 96		Ø 82x96	Ø 82 x 96	Ø 82x96	Ø 82 x 96	Ø 82x96
	3.5	Wheels, number front/back (x=driven)						2/2			
	3.6	Tread width, front	b10 mm					109			
	3.7	Tread width, rear	b11 mm					370			
Basic dimensions	4.4	Lift (h3)	h3 mm					122			
	4.9	Height of tiller handle in drive position min./max.	h14 mm					1234			
	4.15	Height, lowered	h13 mm					86			
	4.19	Total length	l1 mm					1546			
	4.20	Length including fork shank	l2 mm					396			
	4.21.1	total width	b1 mm					540			
	4.22	Fork dimensions	s/ e/l mm					62 x 170 x 1150			
	4.25	Width across forks	b5 mm					540			
	4.32	Ground clearance centre of wheelbase	m2 mm					24			
	4.34.1	Aisle width (pallet 1000×1200 sideways)	Ast mm					1763			
	4.34.2	Aisle width (pallet 800x1200 length)	Ast mm					1813			
	4.35	Turning radius	Wa mm					1303			
Performance data											
	5.3	Lowering speed laden/unladen	m/s					0.09 / 0.02			

The German production facilities in
Norderstedt, Moosburg and Landsberg are
certified as well as our Genuine Parts
Center in Kaltenkirchen.

ISO 9001
ISO 14001

Jungheinrich fork lift trucks meet European
safety requirements.



 **JUNGHEINRICH**