



Vertikalni komisionirni viličar

EKS 110

Dvižna višina: 1000-2800 mm / Nosilnost: 1000 kg

Technical drawing of a vehicle seat and backrest assembly in a side view. The drawing includes the following dimensions and parameters:

- h_4 : Total height from the base to the top of the backrest.
- h_1 : Height from the base to the top of the seat cushion.
- 1008: Height of the seat cushion from the base.
- 220: Width of the seat base.
- y : Horizontal distance from the front edge of the seat base to the center of gravity of the seat.
- l_2 : Horizontal distance from the front edge of the seat base to the pivot point of the backrest.
- l_1 : Horizontal distance from the front edge of the seat base to the pivot point of the headrest.
- h_7 : Height of the seat backrest from the base.
- l : Horizontal distance from the pivot point of the backrest to the center of gravity of the backrest.
- h_3 : Height of the backrest from the base.
- h_9 : Height of the headrest from the base.
- h_{12} : Height of the headrest from the base.
- h_6 : Height of the headrest from the base.
- h_{13} : Height of the base from the ground.
- c : Horizontal distance from the pivot point of the backrest to the center of gravity of the backrest.
- Q : Weight of the backrest.
- s : Horizontal distance from the pivot point of the backrest to the center of gravity of the seat.





Na sliki: EKS 110 L 100 E

	4.34.1	Širina delovnega hodnika (paleta 1000 x 1200, prečno)	Ast mm	3039			3127	3039			3127	
	4.34.2	Delovna širina (paleta 800 x 1200 vzdolžno)	Ast mm	3149			3240	3154			3245	
	4.35	Radij obračanja	Wa mm	1548			1603	1548			1603	
Podatki o zmogljivosti	5.1	Hitrost vožnje z bremenom/brez bremena (Efficiency drivePLUS)	km/h	9 / 10 10 / 13	9 / 9 10 / 12	9 / 9 9,5 / 12	9 / 9 9 / 11	9 / 10 10 / 13	9 / 9 10 / 12	9 / 9 9,5 / 12	9 / 9 9 / 11	
	5.2	Hitrost dvigovanja z bremenom/brez bremena	m/s	0,19 / 0,26	0,15 / 0,2		0,23 / 0,31	0,19 / 0,26	0,15 / 0,2		0,23 / 0,31	
	5.3	Hitrost spuščanja z bremenom/brez bremena	m/s	0,24 / 0,24	0,23 / 0,22		0,28 / 0,26	0,24 / 0,24	0,23 / 0,22		0,28 / 0,26	
	5.7	Vzpenjanje z bremenom/ brez bremena	%	5 / 10								
	5.10	Delovna zavora		Generatorsko								
	5.11	Parkirna zavora		Elektromagnetni vzmetni zavorni sistem								
Elektromotor/elektronika	6.1	Vozni motor, moč S2 60 min	kW	3,2								
	6.2	Dvižni motor, moč pri S3	kW	3		6		3		6		
	6.3	Baterija po DIN 43531/35/36		DIN 43535 B								
	6.4	Napetost baterije, nazivna kapaciteta	V / Ah	24 / 620								
	6.5	Teža baterije	kg	480								
	6.6.1	Poraba energije po ciklu EN	kWh/h	0,42								
Drugo	8.1	Način krmiljenja vožnje		AC								
	10.5	Izvedba krmiljenja		Električni servovolan								
	10.7	Hrupnost po EN12053	dB (A)	61								

- Ta tipski list po direktivi VDI 2198 navaja samo tehnične vrednosti standardnega vozila. Odstopajoča oplaščenja, drugi teleskopi, dodatne naprave ipd. imajo lahko drugačne vrednosti.

- Št. VDI 4.2: L100E z zaščitno streho 2.230 mm.
- Št. VDI 4.5: L100E z zaščitno streho 3230 mm.
- Št. VDI 4.7: L100E in Z100E, zaščitna streha opsijsko.

Jungheinrich, d.o.o.

Korenova cesta 11, 1241 Kamnik

Telefon:

Centrala 01 561 04 80

Prodaja 01 561 04 85

Najem 01 561 04 90

Servis 01 561 04 95

Faks 01 562 17 79

info@jungheinrich.si

www.jungheinrich.si

Certificirane so nemške proizvodne
lokacije v Norderstedtu, Moosburgu in
Landsbergu, ravno tako distribucijski
center originalnih rezervnih delov v
Kaltenkirchnu.

ISO 9001
ISO 14001

Viličarji in vozički podjetja Jungheinrich
ustrezajo evropskim varnostnim
predpisom.

The Jungheinrich logo features a red upward-pointing arrow above the word 'JUNGHEINRICH' in a bold, black, sans-serif font.

JUNGHEINRICH