



## Electric pedestrian pallet truck

**EJE 222–235**

Lift height: 122 mm / Load capacity: 2200-3500 kg



# EJE 222-235



## VDI table

|                            |                |   | Jungheinrich |                 |                   |             |
|----------------------------|----------------|---|--------------|-----------------|-------------------|-------------|
|                            |                |   | EJE 222      | EJE 225         | EJE 235           |             |
| Characteristic             | 1.1            | Manufacturer (abbreviated description)              |              |                 |                   |             |
|                            | 1.2            | Manufacturer's type designation                     |              |                 |                   |             |
|                            | 1.3            | Drive type  |              | electric        |                   |             |
|                            | 1.4            | Operation   |              | Pedestrian      |                   |             |
|                            | 1.5            | Load capacity/load                                  | Q kg         | 2200            | 2500              | 3500        |
|                            | 1.6            | Load centre distance                                | c mm         | 600             |                   |             |
|                            | 1.8            | Load distance, centre of drive axle to fork         | x mm         | 908             | 909               |             |
|                            | 1.9            | Wheelbase   | y mm         | 1351            | 1352              |             |
| Weights                    | 2.1.1          | Service weight (incl. battery)                      | kg           | 535             |                   |             |
|                            | 2.2            | Axle load laden front/rear                          | kg           | 879 / 1870      | 970 / 2072        | 1230 / 2833 |
|                            | 2.3            | Axle load unladen front/rear                        | kg           | 408 / 127       |                   | 430 / 135   |
| Wheels/chassis             | 3.1            | Tyres   |              | -               | Polyurethane (PU) |             |
|                            | 3.2            | Tyre size, front                                    |              | Ø 230 x 70      |                   |             |
|                            | 3.3            | Tyre size, rear                                     |              | Ø 85 x 110      | Ø 85 x 85         |             |
|                            | 3.4            | Additional wheels                                   |              | Ø 100 x 40      |                   |             |
|                            | 3.5            | Wheels, number front/back (x=driven)                |              | 1x + 2 / 2      | 1x + 2 / 4        |             |
|                            | 3.6            | Tread width, front                                  | b10 mm       | 510             |                   |             |
|                            | 3.7            | Tread width, rear                                   | b11 mm       | 363             |                   |             |
| Basic dimensions           | 4.4            | Lift (h3)   | h3 mm        | 122             |                   |             |
|                            | 4.9            | Height of tiller handle in drive position min./max. | h14 mm       | 750 / 1237      |                   |             |
|                            | 4.15           | Height, lowered                                     | h13 mm       | 85              |                   |             |
|                            | 4.19           | Total length  | l1 mm        | 1737            |                   |             |
|                            | 4.20           | Length including fork shank                         | l2 mm        | 587             |                   |             |
|                            | 4.21.1         | total width   | b1 mm        | 724             |                   |             |
|                            | 4.22           | Fork dimensions                                     | s/e/l mm     | 55 x 172 x 1150 |                   |             |
|                            | 4.25           | Width across forks                                  | b5 mm        | 535             |                   |             |
|                            | 4.32           | Ground clearance centre of wheelbase                | m2 mm        | 30              |                   |             |
|                            | 4.34.1         | Aisle width (pallet 1000x1200 sideways)             | Ast mm       | 2338            |                   |             |
|                            | 4.34.2         | Aisle width (pallet 800x1200 length)                | Ast mm       | 2227            |                   |             |
| 4.35                       | Turning radius | Wa mm   | 1532         |                 |                   |             |
| Performance data           | 5.1            | Travel speed laden/unladen                          | km/h         | 6 / 6           |                   | 4 / 6       |
|                            | 5.2            | Lift speed laden/unladen                            | m/s          | 0.05 / 0.07     |                   | 0.04 / 0.07 |
|                            | 5.3            | Lowering speed laden/unladen                        | m/s          | 0.05 / 0.04     |                   | 0.06 / 0.04 |
|                            | 5.8            | Max. gradeability laden/unladen                     | %            | 8 / 20          |                   | 5 / 20      |
|                            | 5.10           | Service brake                                       |              | generative      |                   |             |
| Electric motor/electronics | 6.1            | Drive motor, performance S2 60 min                  | kW           | 1.7             |                   |             |
|                            | 6.2            | Lift motor, performance with S3                     | kW           | 2.2             |                   |             |
|                            | 6.3            | Battery according to DIN 43531/35/36                |              | B               |                   |             |
|                            | 6.4            | Battery voltage/nominal capacity                    | V / Ah       | 24 / 250        |                   |             |
|                            | 6.5            | Battery weight                                      | kg           | 220             |                   |             |
|                            | 6.6            | Energy consumption according to VDI cycle           | kWh/h        | 0               |                   |             |
|                            | 6.6.1          | Energy consumption according to EN cycle            | kWh/h        | 0.35            | 0.37              | 0.4         |
|                            | 6.6.2          | CO2 equivalent according to EN ISO 23308            | kg/h0        | 0.2             |                   |             |

|   |       |   |        |      |      |      |
|---|-------|---|--------|------|------|------|
|   | 6.7   | Throughput                                | t/h    | 123  | 148  | 205  |
|   | 6.8.1 | Energy consumption with max. throughput   | kWh/h  | 0.77 | 0.82 | 1.14 |
| Other   | 8.1   | Type of drive control                     |        | AC   |      |      |
|   | 10.7  | Sound pressure level according to EN12053 | dB (A) | 70   |      |      |
| - This data sheet according to VDI guideline 2198 only states the technical values of the standard truck. Different tyres, other masts, additional equipment etc. may result in different values. |       |   |        |      |      |      |

- 4.33: lowered load section: + 50 mm
- 1.8: 1.9: 4.35: lowered load section: + 56 mm
- 4.34: lowered load section: + 25 mm
- 1.9: 4.19: 4.19.1: 4.20: 4.33: 4.34: 4.35: with lateral battery exchange: L / M LBE = M + 72 mm; L LBE = M + 125 mm
- 5.1: up to a load of 3 t: max. travel speed = 6 km/h.

The German production facilities in  
Norderstedt, Moosburg and Landsberg are  
certified as well as our Genuine Parts  
Center in Kaltenkirchen.

ISO 9001  
ISO 14001

Jungheinrich fork lift trucks meet European  
safety requirements.



 **JUNGHEINRICH**

The Jungheinrich logo, featuring a red upward-pointing arrow above the word 'JUNGHEINRICH' in a bold, black, sans-serif font.