





Electric ride-on/pedestrian pallet truck



ERE 120–230

Lift height: 122 mm / Load capacity: 2000-3000 kg

JUNGHEINRICH

ERE 120–230





VDI table

Characteristic	1.1	Manufacturer (abbreviated description)			Jungheinrich				
	1.3	Drive			Electric				
	1.4	Operation			Tiller				
	1.5	Load capacity/load	Q	kg	2000	2500			
	1.6	Load centre distance	c	mm	600				
	1.8	Load distance, centre of drive axle to fork	x	mm	908				
	1.9	Wheelbase	y	mm	1378				
Weights	2.1	tare weight		kg	400	404			
	2.1.1	Service weight (incl. battery)		kg	630	634			
	2.2	Axle load laden front/rear		kg	795 / 1825	1126 / 2090			
	2.3	Axle load unladen front/rear		kg	474 / 138	550 / 159			
Wheels/suspension system	3.1	Tyres			Vulkollan ®/PU + quartz/Vulkollan ®				
	3.2	Tyre size, front			Ø 230 x 65	Ø 230 x 77			
	3.3	Tyre size, rear			Ø 85 x 110 / Ø 85 x 85				
	3.4	Additional wheels			Ø 140 x 57				
	3.5	Wheels, number front/back (x=driven)			1x +2/2 oder 4				
	3.6	Tread width, front	b10	mm	363				
	3.7	Tread width, rear	b11	mm	512				
Basic dimensions	4.4	Lift (h3)	h3	mm	122				
	4.9	Height of tiller handle in drive position min./max.	h14	mm	1137 / 1419				
	4.15	Height, lowered	h13	mm	85				
	4.19	total length	l1	mm	1847				
	4.20	Length including fork shank	l2	mm	697				
	4.21.1	total width	b1	mm	770				
	4.22	Fork dimensions	s/e/l	mm	55 x 172 x 1150				
	4.25	Width across forks	b5	mm	535				
	4.32	Ground clearance centre of wheelbase	m2	mm	30				
	4.34.1	Aisle width (pallet 1000×1200 sideways)	Ast	mm	2411				
	4.34.2	Aisle width (pallet 800x1200 length)	Ast	mm	2299				
	4.34.8	Aisle width (pallet 800×1200 crosswise)	Ast	mm	2414				
	4.35	Turning radius	Wa	mm	1604				
Performance data	5.1	Travel speed laden/unladen		km/h	6 / 6	8 / 9	9 / 9	9.5 / 12.5	9.5 / 14
	5.2	Lift speed laden/unladen		m/s	0.04 / 0.04		0.05 / 0.07		
	5.3	Lowering speed laden/unladen		m/s	0.05 / 0.04		0.05 / 0.05		
	5.8	Max. gradeability laden/unladen		%	5 / 7	8 / 16			
	5.10	Service brake			generative				

E-motor/Electronics	6.1	Drive motor, performance S2 60 min	kW	2		2.8		3.2
	6.2	Lift motor, performance with S3	kW	1.2		2.2		
	6.3	Battery according to DIN 43531/35/36		B	-			
	6.4	Battery voltage/nominal capacity	V / Ah	24 / 250				
	6.5	Battery weight	kg	230				
	6.6.1	Energy consumption according to EN cycle	kWh/h	0.4	0.43	0.4	0.35	0.39
	6.6.2	CO2 equivalent according to EN ISO 23308	kg/h0	0.22	0.23	0.22	0.19	0.21
	6.7	Throughput	t/h	114	142	156	184	222
	6.8.1	Energy consumption with max. throughput	kWh/h	0.74	1.11	1.18	1.29	1.89
Other	8.1	Type of drive control		AC				
	10.7	Sound pressure level according to EN12053	dB (A)	63		64		67
- This data sheet according to VDI guideline 2198 only states the technical values of the standard truck. Different tyres, other masts, additional equipment etc. may result in different values.								

The values in the table apply to the folding stand-on platform (folded up), M-LBE battery compartment, fork length 1,150 mm, raised support arm lift.

- VDI no. 1.8: lowered load section: $x + 56$ mm.
 - VDI no. 1.9: lowered load section: $y + 56$ mm. With M-VBE, L-LBE & L high-LBE battery compartment: $y + 72$ mm; L-VBE: $y + 125$ mm.
 - VDI no. 2.1: with lateral battery exchange: $+ 25$ kg.
 - VDI no. 4.19: with M-VBE, L-LBE & L high-LBE battery compartment: $l1 + 72$ mm; L-VBE: $l1 + 125$ mm. With folding platform folded down: $l1 + 416$ mm; compact, fixed platform: $l1 + 357$ mm; extended, fixed platform: $l1 + 472$ mm; L platform: $l1 + 477$ mm.
 - VDI no. 4.20: with M-VBE, L-LBE & L high-LBE battery compartment: $l2 + 72$ mm; L-VBE: $l2 + 125$ mm. With folding platform folded down: $l2 + 416$ mm; compact, fixed platform: $l2 + 357$ mm; extended, fixed platform: $l2 + 472$ mm; L platform: $l2 + 477$ mm.
 - VDI no. 4.34.1: lowered load section: aisle width $+ 50$ mm. with folding platform folded down: aisle width $+ 416$ mm; compact, fixed platform: aisle width $+ 357$ mm; extended, fixed platform: aisle width $+ 472$ mm; L platform: aisle width $+ 477$ mm.
 - VDI no. 4.34.2: with folding platform folded down: aisle width $+ 416$ mm; compact, fixed platform: aisle width $+ 357$ mm; extended, fixed platform: aisle width $+ 472$ mm; L platform: aisle width $+ 477$ mm.
 - VDI no. 4.34.8: lowered load section: aisle width $+ 68$ mm. with folding platform folded down: aisle width $+ 416$ mm; compact, fixed platform: aisle width $+ 357$ mm; extended, fixed platform: aisle width $+ 472$ mm; L platform: aisle width $+ 477$ mm.
 - VDI no. 4.35: lowered load section: $Wa + 56$ mm.
- With M-VBE, L-LBE & L high-LBE battery compartment: $Wa + 72$ mm; L-VBE: $Wa + 125$ mm. with folding platform folded down: $Wa + 416$ mm; compact, fixed platform: $Wa + 357$ mm; extended, fixed platform: $Wa + 472$ mm; L platform: $Wa + 477$ mm.
- VDI no. 5.1: ERE 230: 9.5 km/h with 2.5 t load.

The German production facilities in
Norderstedt, Moosburg and Landsberg are
certified as well as our Genuine Parts
Center in Kaltenkirchen.

ISO 9001
ISO 14001

Jungheinrich fork lift trucks meet European
safety requirements.



 **JUNGHEINRICH**