



Electric pedestrian stacker with support arm lift

ERD 120/220/220 drivePLUS

Lift height: 1500-2905 mm / Load capacity: 2000 kg



ERD 120/220/220 drivePLUS





ERD 120/220/220 drivePLUS

| ERD 120, ERD 220, ERD 220 drivePLUS | Lift (h3) | Retracted mast height (h1) | Free lift (h2) | Extended mast height (h4) |
|-------------------------------------|-----------|----------------------------|----------------|---------------------------|
| Single mast E | 1500 mm | 1921 mm | 1468 mm | 1953 mm |
| | 1660 mm | 2081 mm | 1628 mm | 2113 mm |
| Triplex mast DT | 2050 mm | 1213 mm | 100 mm | 2513 mm |
| | 2350 mm | 1313 mm | 100 mm | 2813 mm |

VDI table

| | | | | | | |
|--------------------------|--------------------------------------|---|----------|-----------------------|------------|----------|
| Characteristic | 1.1 | Manufacturer (abbreviated description) | | Jungheinrich | | |
| | 1.3 | Drive | | Electric | | |
| | 1.4 | Operation | | Stand-on/pedestrian | | |
| | 1.5 | Load capacity/load | Q kg | 2000 | | |
| | 1.5.1 | Rated capacity/load with mast lift | Q kg | 1000 | | |
| | 1.5.2 | Rated capacity/load with support arm lift | Q kg | 2000 | | |
| | 1.6 | Load centre distance | c mm | 600 | | |
| | 1.8 | Load distance, centre of drive axle to fork | x mm | 956 | | |
| | 1.9 | Wheelbase | y mm | 1624 | | |
| Weights | 2.1.1 | Service weight (incl. battery) | kg | 1010 | | |
| | 2.2 | Axle load laden front/rear | kg | 1185 / 1830 | | |
| | 2.3 | Axle load unladen front/rear | kg | 750 / 260 | | |
| Wheels/suspension system | 3.1 | Tyres | | Polyurethane (PU) | | |
| | 3.2 | Tyre size, front | | ø 230 x 65 | ø 230 x 77 | |
| | 3.3 | Tyre size, rear | | ø 85 x 95 / ø 85 x 75 | | |
| | 3.4 | Additional wheels | | ø 140 x 50 | | |
| | 3.5 | Wheels, number front/back (x=driven) | | 1x + 2 / 2 oder 4 | | |
| | 3.6 | Tread width, front | b10 mm | 512 | | |
| | 3.7 | Tread width, rear | b11 mm | 385 | | |
| Basic dimensions | 4.2 | Retracted mast height (h1) | h1 mm | 1306 | | |
| | 4.3 | Free lift (h2) | h2 mm | 100 | | |
| | 4.4 | Lift (h3) | h3 mm | 1660 | | |
| | 4.5 | Extended mast height (h4) | h4 mm | 2115 | | |
| | 4.6 | Initial lift | h5 mm | 110 | | |
| | 4.9 | Height of tiller handle in drive position min./max. | h14 mm | 1230 / 1410 | | |
| | 4.15 | Height, lowered | h13 mm | 90 | | |
| | 4.19 | total length | l1 mm | 2084 | | |
| | 4.20 | Length including fork shank | l2 mm | 894 | | |
| | 4.21.1 | total width | b1 mm | 770 | | |
| | 4.22 | Fork dimensions | s/e/l mm | 56 x 185 x 1190 | | |
| | 4.25 | Width across forks | b5 mm | 570 | | |
| | 4.32 | Ground clearance centre of wheelbase | m2 mm | 19 | | |
| | 4.34.1 | Aisle width (pallet 1000x1200 sideways) | Ast mm | 2300 | | |
| 4.34.2 | Aisle width (pallet 800x1200 length) | Ast mm | 2310 | | | |
| 4.35 | Turning radius | Wa mm | 1866 | | | |
| Performance data | 5.1 | Travel speed laden/unladen | km/h | 8.2 / 9 | 9.5 / 12.5 | 9.5 / 14 |
| | 5.2 | Lift speed laden/unladen | m/s | 0.17 / 0.32 | | |
| | 5.3 | Lowering speed laden/unladen | m/s | 0.45 / 0.35 | | |
| | 5.7 | Gradeability laden/unladen | % | 8 / 16 | | 10 / 20 |
| | 5.10 | Service brake | | generative | | |

| | | | | | | |
|---------------------|-------|---|--------|-------------|------|------|
| E-motor/Electronics | 6.1 | Drive motor, performance S2 60 min | kW | 2 | 2.8 | 3.2 |
| | 6.2 | Lift motor, performance with S3 | kW | 2.2 | | |
| | 6.3 | Battery according to DIN 43531/35/36 | | DIN 43535 B | | |
| | 6.4 | Battery voltage/nominal capacity | V / Ah | 24 / 250 | | |
| | 6.5 | Battery weight | kg | 235 | | |
| | 6.6 | Energy consumption according to VDI cycle | kWh/h | 0 | | |
| | 6.6.1 | Energy consumption according to EN cycle | kWh/h | 0.68 | 0.62 | 0.71 |
| | 6.6.2 | CO2 equivalent according to EN ISO 23308 | kg/h0 | 0.37 | 0.34 | 0.38 |
| | 6.7 | Throughput | t/h | 84 | 108 | |
| | 6.8.1 | Energy consumption with max. throughput | kWh/h | 0.83 | 1.44 | 1.48 |
| Other | 8.1 | Type of drive control | | AC | | |
| | 10.7 | Sound pressure level according to EN12053 | dB (A) | 71 | 68 | 67 |

- This data sheet according to VDI guideline 2198 only states the technical values of the standard truck. Different tyres, other masts, additional equipment etc. may result in different values.

The values in the table apply to the folding stand-on platform (folded up), M-LBE battery compartment, ZT1660 mast, proportional hydraulics, fork length 1,190 mm, raised support arm lift.

- VDI no. 1.5: in double-decker operation: mast lift max. 1 t / total load max. 2 t. Permitted up to a lift height $h_{13} + h_3$ of 1,800 mm. The heavier load is to be transported on the support arms (below).
- VDI no. 1.8: lowered support arm lift: $x + 48$ mm. With fork length 1,150 mm: $x - 40$ mm. With simplex mast: $x - 1$ mm; triplex telescopic mast: $x - 10$ mm; ZZ mast: $x - 29$ mm.
- VDI no. 1.9: lowered support arm lift: $y + 48$ mm. With fork length 1,150 mm: $y - 40$ mm. With M-VBE, L-LBE & L high-LBE battery compartment: $y + 72$ mm; L-VBE: $y + 117$ mm.
- VDI no. 4.9: with fixed stand-on platform: 1,256 mm (1,296 mm with L high-LBE battery compartment) or 1,204 / 1,284 mm with height-adjustable tiller.
- VDI no. 4.19: with M-VBE, L-SBE & L-high SBE battery compartment: $l_1 + 72$ mm; L-VBE: $l_1 + 117$ mm. With folding platform folded down: $l_1 + 396$ mm; compact, fixed platform: $l_1 + 357$ mm; extended, fixed platform: $l_1 + 472$ mm; L platform: $l_1 + 477$ mm. With simplex mast: $l_1 + 1$ mm; triplex telescopic mast: $l_1 + 10$ mm; ZZ mast: $l_1 + 29$ mm.
- VDI no. 4.20: with M-VBE, L-SBE & L-high SBE battery compartment: $l_2 + 72$ mm; L-VBE: $l_2 + 117$ mm. With folding platform folded down: $l_2 + 396$ mm; compact, fixed platform: $l_2 + 357$ mm; extended, fixed platform: $l_2 + 472$ mm; L platform: $l_2 + 477$ mm. With simplex mast: $l_2 + 1$ mm; triplex telescopic mast: $l_2 + 10$ mm; ZZ mast: $l_2 + 29$ mm.
- VDI no. 4.34.1: with fork length 1,150 mm: aisle width - 40 mm. With M-VBE, L-LBE & L high-LBE battery compartment: aisle width + 72 mm; L-VBE: aisle width + 117 mm. With folding platform folded down: aisle width + 396 mm; compact, fixed platform: aisle width + 357 mm; extended, fixed platform: aisle width + 472 mm; L platform: aisle width + 477 mm. With simplex mast: aisle width + 1 mm; triplex telescopic mast: aisle width + 10 mm; ZZ mast: aisle width + 29 mm.
- VDI no. 4.34.2: with fork length 1,150 mm: aisle width - 40 mm. With M-VBE, L-LBE & L high-LBE battery compartment: aisle width + 72 mm; L-VBE: aisle width + 117 mm. With folding platform folded down: aisle width + 396 mm; compact, fixed platform: aisle width + 357 mm; extended, fixed platform: aisle width + 472 mm; L platform: aisle width + 477 mm. With simplex mast: aisle width + 1 mm; triplex telescopic mast: aisle width + 10 mm; ZZ mast: aisle width + 29 mm.
- VDI no. 4.35: with fork length 1,150 mm: $W_a - 40$ mm. With M-VBE, L-SBE & L-high SBE battery compartment: $W_a + 72$ mm; L-VBE: $W_a + 117$ mm. With folding platform folded down: $W_a + 396$ mm; compact, fixed platform: $W_a + 357$ mm; extended, fixed platform: $W_a + 472$ mm; L platform: $W_a + 477$ mm.
- VDI no. 5.3: With black / white hydraulics: 0.26 / 0.27 m/s.
- VDI no. 6.2: With black / white hydraulics: 1.9 kW.
- VDI no. 5.1: maximum travel speed in double-decker operation (mast lift > 400 mm): ERD 120: 6 km/h; ERD 220 / 220 drivePLUS: 8.2 km/h.

The German production facilities in
Norderstedt, Moosburg and Landsberg are
certified as well as our Genuine Parts
Center in Kaltenkirchen.

ISO 9001
ISO 14001

Jungheinrich fork lift trucks meet European
safety requirements.



 **JUNGHEINRICH**

The Jungheinrich logo, featuring a red upward-pointing arrow above the word 'JUNGHEINRICH' in a bold, black, sans-serif font.