



Electric pedestrian pallet truck

AME 15

Lift height: 115 mm / Load capacity: 1500 kg

Powerful and lightweight

Unstoppable in the store, in production, as well as in and on HGVs.

The Jungheinrich AME 15 pallet trucks are the optimal solution for tight spaces and weight-sensitive work environments. With their high manoeuvrability and robust performance, they easily master demanding logistics processes.

The combination of compact dimensions and low service weight makes them the first choice for daily in-house pallet transport and HGV transport. Their intuitive operation and one-handed operation from both sides make every task easier.

Thanks to their high driving and cornering stability, the Jungheinrich AME 15 pedestrian pallet trucks operate with maximum safety in everyday work. A reinforced steel construction and protected support wheels make them extremely robust and durable.

Their high efficiency is an additional advantage: low energy consumption based on the latest lithium-ion technology, the option of intermediate charging and the maintenance-free drive motor ensure high availability in daily operation.

All benefits at a glance

- Powerful mid-range electric pedestrian pallet truck, ideal for use on HGVs.
- Intuitive and safe operation, along with high driving and cornering stability.
- Optimised robustness thanks to reinforced steel construction and protected support wheels.
- Li-ion battery and low energy consumption for high availability.
- Proven Jungheinrich quality with durable components.

Your Jungheinrich pallet trucks

for maximum customer benefits.



Efficiency

Maximum performance with the most efficient trucks.

Maintenance-free, robust and economical in daily operations.

Ideal for daily operations

- Low energy consumption.
- Maintenance-free drive motor.
- Lightweight, agile and compact.
- Improved robustness and performance.

Optimal energy efficiency

- Efficient charging processes without expensive charging infrastructure.
- Cost-efficient due to longer life cycles.
- Flexible use thanks to booster charging of the lithium-ion battery.
- Easy charging at any socket using the supplied charger.
- Automatic cut-out when not in use to save costs and protect the environment.

Proven lithium-ion technology

- Zero maintenance saves time and money.
- Rapid and booster charging ensures high truck availability.
- Up to three times the lifespan in comparison with lead-acid batteries.
- Safe to use thanks to high-quality battery management system.




Safety

Best prerequisites for working safely.

Easy handling and sophisticated protection for people, machinery and goods.

Intuitive and comfortable to operate

- Two sprung support wheels located next to the drive wheel enhance stability.
- Safe and sensitive manoeuvring thanks to well-coordinated software and chassis.
- High gradeability: 8%.
- Fully integrated, protected support wheels.
- Slow travel button for manoeuvring.
- Two travel programs for adjusted speeds (2.5 km/h and 5.5 km/h).
- Precise control of fork insertion depth prevents damage to pallets and trucks.
- Tandem fork rollers plus protected entry rollers for comfortable transverse lifting of pallets.



Individuality

A forklift truck as individual as your business.

With the robust Jungheinrich AME 15 electric pedestrian pallet truck, you can transport goods flexibly and reliably both indoors and outdoors.

Universal and versatile

- Tiller head with double-sided one-handed operation.
- Truck status visible via prominent LED strips.
- Easy access via PIN code.
- All control instruments including display are neatly integrated into the tiller.
- Fork marking at 800 mm for precise transverse lifting of pallets.
- Various fork lengths available.

Overview

The right solution for your applications:

Name	Load capacity/ load	Lift height (max.)	Travel speed unladen	Aisle width (pallet 800x1200 length)	Lift speed unladen	total height
AME 15 (540x800)	1500 kg	115 mm	5.5 km/h	1958 mm	0.04 m/s	673 mm
AME 15 (540x1000)	1500 kg	115 mm	5.5 km/h	2003 mm	0.04 m/s	673 mm
AME 15 (540x1150)	1500 kg	115 mm	5.5 km/h	2060 mm	0.04 m/s	673 mm
AME 15 (530x1150, V- BV, LG)	1500 kg	115 mm	5.5 km/h	2060 mm	0.04 m/s	673 mm
AME 15 (540x1150)	1500 kg	115 mm	5.5 km/h	2060 mm	0.04 m/s	673 mm
AME 15 (685x1000)	1500 kg	115 mm	5.5 km/h	2003 mm	0.04 m/s	673 mm
AME 15 (685x1150)	1500 kg	115 mm	5.5 km/h	2060 mm	0.04 m/s	673 mm
AME 15 (685x1150)	1500 kg	115 mm	5.5 km/h	2060 mm	0.04 m/s	673 mm

The German production facilities in
Norderstedt, Moosburg and Landsberg are
certified as well as our Genuine Parts
Center in Kaltenkirchen. ISO 9001
ISO 14001

 **JUNGHEINRICH**