





## **Electric ride-on/pedestrian pallet truck** **ERE 120–230**

Lift height: 122 mm / Load capacity: 2000-3000 kg

***JUNGHEINRICH***

# ERE 120–230





## VDI table

|                  |                  |                                                     |                            |                                     |                |             |             |                   |             |                   |        |
|------------------|------------------|-----------------------------------------------------|----------------------------|-------------------------------------|----------------|-------------|-------------|-------------------|-------------|-------------------|--------|
| Characteristic   | 1.1              | Manufacturer (abbreviated description)              |                            | Jungheinrich                        |                |             |             |                   |             |                   |        |
|                  | 1.2              | Manufacturer's type designation                     |                            | ERE 120 6km/h                       | ERE 120 9 km/h | ERE 125     | ERE 225     | ERE 225 drivePLUS | ERE 230     | ERE 230 drivePLUS |        |
|                  | 1.3              | Drive type                                          |                            | electric                            |                |             |             |                   |             |                   |        |
|                  | 1.4              | Operation                                           |                            | Tiller                              |                |             |             |                   |             |                   |        |
|                  | 1.5              | Load capacity/load                                  | Q kg                       | 2000                                |                | 2500        |             |                   | 3000        |                   |        |
|                  | 1.6              | Load centre distance                                | c mm                       | 600                                 |                |             |             |                   |             |                   |        |
|                  | 1.8              | Load distance, centre of drive axle to fork         | x mm                       | 908                                 |                |             |             |                   |             |                   |        |
|                  | 1.9              | Wheelbase                                           | y mm                       | 1378                                |                |             |             |                   |             | 1450              |        |
|                  | Weights          | 2.1                                                 | Netto weight               | kg                                  | 400            |             | 404         |                   |             | 424               |        |
| 2.1.1            |                  | Service weight (incl. battery)                      | kg                         | 630                                 |                | 634         |             |                   | 721         |                   |        |
| 2.2              |                  | Axle load laden front/rear                          | kg                         | 795 / 1825                          |                | 1126 / 2090 |             |                   | 1239 / 2494 |                   |        |
| 2.3              |                  | Axle load unladen front/rear                        | kg                         | 474 / 138                           |                | 550 / 159   |             |                   | 565 / 160   |                   |        |
|                  |                  |                                                     |                            |                                     |                |             |             |                   |             |                   |        |
| Wheels/chassis   | 3.1              | Tyres                                               |                            | Vulkollan ®/PU + quartz/Vulkollan ® |                |             |             |                   |             |                   |        |
|                  | 3.2              | Tyre size, front                                    |                            | Ø 230 x 65                          |                | Ø 230 x 77  |             |                   |             |                   |        |
|                  | 3.3              | Tyre size, rear                                     |                            | Ø 85 x 110 / Ø 85 x 85              |                |             |             |                   |             | Ø 85 x 85         |        |
|                  | 3.4              | Additional wheels                                   |                            | Ø 140 x 57                          |                |             |             |                   |             |                   |        |
|                  | 3.5              | Wheels, number front/back (x=driven)                |                            | 1x +2/2 oder 4                      |                |             |             |                   |             | 1x +2/4           |        |
|                  | 3.6              | Tread width, front                                  | b10 mm                     | 363                                 |                |             |             |                   |             |                   |        |
|                  | 3.7              | Tread width, rear                                   | b11 mm                     | 512                                 |                |             |             |                   |             |                   |        |
| Basic dimensions | 4.4              | Lift (h3)                                           | h3 mm                      | 122                                 |                |             |             |                   |             |                   |        |
|                  | 4.9              | Height of tiller handle in drive position min./max. | h14 mm                     | 1137 / 1419                         |                |             |             |                   |             |                   |        |
|                  | 4.15             | Height, lowered                                     | h13 mm                     | 85                                  |                |             |             |                   |             |                   |        |
|                  | 4.19             | Total length                                        | l1 mm                      | 1847                                |                |             |             |                   | 1919        |                   |        |
|                  | 4.20             | Length including fork shank                         | l2 mm                      | 697                                 |                |             |             |                   | 769         |                   |        |
|                  | 4.21.1           | total width                                         | b1 mm                      | 770                                 |                |             |             |                   |             |                   |        |
|                  | 4.22             | Fork dimensions                                     | s/ e/l mm                  | 55 x 172 x 1150                     |                |             |             |                   |             |                   |        |
|                  | 4.25             | Width across forks                                  | b5 mm                      | 535                                 |                |             |             |                   |             |                   |        |
|                  | 4.32             | Ground clearance centre of wheelbase                | m2 mm                      | 30                                  |                |             |             |                   |             |                   |        |
|                  | 4.34.1           | Aisle width (pallet 1000×1200 sideways)             | Ast mm                     | 2411                                |                |             |             |                   | 2483        |                   |        |
|                  | 4.34.2           | Aisle width (pallet 800x1200 length)                | Ast mm                     | 2299                                |                |             |             |                   | 2372        |                   |        |
|                  | 4.34.8           | Aisle width (pallet 800×1200 crosswise)             | Ast mm                     | 2414                                |                |             |             |                   | 2486        |                   |        |
|                  | 4.35             | Turning radius                                      | Wa mm                      | 1604                                |                |             |             |                   | 1677        |                   |        |
|                  | Performance data | 5.1                                                 | Travel speed laden/unladen | km/h                                | 6 / 6          | 8 / 9       | 9 / 9       | 9.5 / 12.5        | 9.5 / 14    | 6 / 12.5          | 6 / 14 |
| 5.2              |                  | Lift speed laden/unladen                            | m/s                        | 0.04 / 0.04                         |                |             | 0.05 / 0.07 |                   |             |                   |        |
| 5.3              |                  | Lowering speed laden/unladen                        | m/s                        | 0.05 / 0.04                         |                |             | 0.05 / 0.05 |                   |             |                   |        |
| 5.8              |                  | Max. gradeability laden/unladen                     | %                          | 5 / 7                               | 8 / 16         |             |             |                   |             | 6 / 16            |        |
| 5.10             |                  | Service brake                                       |                            | generative                          |                |             |             |                   |             |                   |        |

|                                                                                                                                                                                                   |       |                                           |        |          |      |      |      |      |      |      |  |          |  |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------|-------------------------------------------|--------|----------|------|------|------|------|------|------|--|----------|--|
| Electric motor/electronics                                                                                                                                                                        | 6.1   | Drive motor, performance S2 60 min        | kW     | 2        |      | 2.8  |      | 3.2  |      | 2.8  |  | 3.2      |  |
|                                                                                                                                                                                                   | 6.2   | Lift motor, performance with S3           | kW     | 1.2      |      | 2.2  |      |      |      |      |  |          |  |
|                                                                                                                                                                                                   | 6.3   | Battery according to DIN 43531/35/36      |        | B        |      | -    |      |      |      |      |  | B        |  |
|                                                                                                                                                                                                   | 6.4   | Battery voltage/nominal capacity          | V / Ah | 24 / 250 |      |      |      |      |      |      |  | 24 / 375 |  |
|                                                                                                                                                                                                   | 6.5   | Battery weight                            | kg     | 230      |      |      |      |      |      |      |  | 297      |  |
|                                                                                                                                                                                                   | 6.6.1 | Energy consumption according to EN cycle  | kWh/h  | 0.4      | 0.43 | 0.4  | 0.35 | 0.39 | 0.36 | 0.41 |  |          |  |
|                                                                                                                                                                                                   | 6.6.2 | CO2 equivalent according to EN ISO 23308  | kg/h   | 0.22     | 0.23 | 0.22 | 0.19 | 0.21 | 0.19 | 0.22 |  |          |  |
|                                                                                                                                                                                                   | 6.7   | Throughput                                | t/h    | 114      | 142  | 156  | 184  | 222  | 220  | 266  |  |          |  |
|                                                                                                                                                                                                   | 6.8.1 | Energy consumption with max. throughput   | kWh/h  | 0.74     | 1.11 | 1.18 | 1.29 | 1.89 | 1.45 | 2.05 |  |          |  |
| Other                                                                                                                                                                                             | 8.1   | Type of drive control                     |        | AC       |      |      |      |      |      |      |  |          |  |
|                                                                                                                                                                                                   | 10.7  | Sound pressure level according to EN12053 | dB (A) | 63       |      |      | 64   | 67   | 64   | 67   |  |          |  |
| - This data sheet according to VDI guideline 2198 only states the technical values of the standard truck. Different tyres, other masts, additional equipment etc. may result in different values. |       |                                           |        |          |      |      |      |      |      |      |  |          |  |

The values in the table apply to the folding stand-on platform (folded up), M-LBE battery compartment, fork length 1,150 mm, raised support arm lift.

- VDI no. 1.8: lowered load section:  $x + 56$  mm.
  - VDI no. 1.9: lowered load section:  $y + 56$  mm. With M-VBE, L-LBE & L high-LBE battery compartment:  $y + 72$  mm; L-VBE:  $y + 125$  mm.
  - VDI no. 2.1: with lateral battery exchange:  $+ 25$  kg.
  - VDI no. 4.19: with M-VBE, L-LBE & L high-LBE battery compartment:  $l1 + 72$  mm; L-VBE:  $l1 + 125$  mm. With folding platform folded down:  $l1 + 416$  mm; compact, fixed platform:  $l1 + 357$  mm; extended, fixed platform:  $l1 + 472$  mm; L platform:  $l1 + 477$  mm.
  - VDI no. 4.20: with M-VBE, L-LBE & L high-LBE battery compartment:  $l2 + 72$  mm; L-VBE:  $l2 + 125$  mm. With folding platform folded down:  $l2 + 416$  mm; compact, fixed platform:  $l2 + 357$  mm; extended, fixed platform:  $l2 + 472$  mm; L platform:  $l2 + 477$  mm.
  - VDI no. 4.34.1: lowered load section: aisle width  $+ 50$  mm. with folding platform folded down: aisle width  $+ 416$  mm; compact, fixed platform: aisle width  $+ 357$  mm; extended, fixed platform: aisle width  $+ 472$  mm; L platform: aisle width  $+ 477$  mm.
  - VDI no. 4.34.2: with folding platform folded down: aisle width  $+ 416$  mm; compact, fixed platform: aisle width  $+ 357$  mm; extended, fixed platform: aisle width  $+ 472$  mm; L platform: aisle width  $+ 477$  mm.
  - VDI no. 4.34.8: lowered load section: aisle width  $+ 68$  mm. with folding platform folded down: aisle width  $+ 416$  mm; compact, fixed platform: aisle width  $+ 357$  mm; extended, fixed platform: aisle width  $+ 472$  mm; L platform: aisle width  $+ 477$  mm.
  - VDI no. 4.35: lowered load section:  $Wa + 56$  mm.
- With M-VBE, L-LBE & L high-LBE battery compartment:  $Wa + 72$  mm; L-VBE:  $Wa + 125$  mm. with folding platform folded down:  $Wa + 416$  mm; compact, fixed platform:  $Wa + 357$  mm; extended, fixed platform:  $Wa + 472$  mm; L platform:  $Wa + 477$  mm.
- VDI no. 5.1: ERE 230: 9.5 km/h with 2.5 t load.

The German production facilities in  
Norderstedt, Moosburg and Landsberg are  
certified as well as our Genuine Parts  
Center in Kaltenkirchen.

ISO 9001  
ISO 14001

Jungheinrich fork lift trucks meet European  
safety requirements.



 **JUNGHEINRICH**