Automated Guided Vehicles.

JUNGHEINRICH

© © © ©

Indicators for use.



26

AGV – fully automatic, precise and reliable.

Based on tried-and-tested series trucks and controlled by intelligent software, Automated Guided Vehicles (AGVs) are the beating heart of automated logistics. They perform recurring tasks with large handling volumes across the entire production

and storage area fully automatically, precisely and reliably. Extensive safety sensors protect people, load and machines. This enables use of the automated vehicles in mixed operation.

HIGH-RACK STACKER ETX 513a / 515a

Flexible AGV for manual, semi-automatic or automatic use in high-bay warehouses:

- "Man-down" high-rack stacker
- Lift height up to 13.000 mm
- Load capacity up to 1.500 kg

PALLET TRUCK

ERE 225a

Powerful AGV, suitable for standardised load aids, multi-pallet transport and long distances:

- Multi-pallet transport
- Fork length up to 2,400 mm
- Load capacity up to 2,500 kg

1

Primary indicators for AGVs

- Multi-shift operation
- Continuous transport
- Standard loading devices (e.g. euro pallets, industrial pallets, lattice boxes)
- Lift heights up to 6 m / up to 13 m for automatic high-rack stackers

COUNTERBALANCE TRUCK

Versatile AGV suitable for closed loading

Frequent transport damage caused by "manual transport"

EKX 514a / 516ka / 516a

warehouse:

- devices and for non-accessible stations:

17

Adjustable forks

EKS 215a

- Lift height up to 6,000 mm Load capacity up to 1,500 kg

ERC 213a / 217a

Highly manoeuvrable AGV suitable for standardised load aids and accessible stations:

- Low space requirement
- ► Lift height up to 4,400 mm
- ► Load capacity up to 1,700 kg







Comprehensive safety sensors for use in mixed operation

A high degree of efficiency in multi-shift opera-tion thanks to intelligent energy management.

STACKER TRUCK

Conditions of use for AGVs

- Enclosed, dry hall
- ► Hall temperature: 5 to 35 °C
- Lane width from 2 m (single lane) for automated trucks Aisle width 1.8 m and transfer aisle 6 m for automatic high-rack stackers
- Industrial floors / narrow aisle floor for automatic high-rack stackers

HIGH-RACK STACKER

Powerful AGV with the option of step-bystep automation of the very narrow aisle

"Man-up" high-rack stacker Lift height up to 13.000 mm Load capacity up to 1.600 kg

TOW TRACTOR

EZS 350a

Robust towing truck, suitable for towing

- Complete manual and automated



verything from a single source: from pl and implementation to service and sup

ISO 9001 The German production facilities in Norderstedt, Moosburg and Landsberg are certified.



Jungheinrich Aktiengesellschaft

Friedrich-Ebert-Damm 129 22047 Hamburg Germany Telephone +49 40 6948-0 Telefax +49 40 6948-1777

info@jungheinrich.com www.jungheinrich.com

